

test pipe plugs

https://ehle-hd.com/en/product/_trashed/



The **test pipe plugs** are mechanical pipe stops used to seal or test pipes or water lines. Applicable in industrial plants, ship building and equipment construction. Our pressure pistons are also available as test component with pressure gauge or as a bleeding component.

Version is size dependent:

- DN 14 - 75 available as plug with one sealing ring
- DN 80 - 300 as aluminum discs with two sealing rings









Features









- to seal off and test pipe lines, for industrial facilities, shipbuilding and technical installations
- also upgradeable as test or bleeding components
- a hollow spindle generates the pressure
- the plugs have a ball valve to shut off the test chamber









Only use pipe stops with support installed and consider the maximum backpressure. Never exceed the maximum pressure specified!

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2000500	test pipe plug - Ø 14	clamping range: 14-16 mm construction: 1 sealing ring bypass: 3 mm max. backpressure: 30 bar (435 psi)	235 × 14 × 14 mm 0.20
	2000502	test pipe plug - Ø 20	clamping range: 20-25 mm construction: 1 sealing ring bypass: 4 mm max. backpressure: 30 bar (435 psi)	240 × 20 × 20 mm 0.26
	2000503	test pipe plug - Ø 25	clamping range: 25-30 mm construction: 1 sealing ring bypass: 4 mm max. backpressure: 30 bar (435 psi)	280 × 25 × 25 mm 0.28
	2000504	test pipe plug - Ø 30	clamping range: 30-35 mm construction: 1 sealing ring bypass: 8 mm max. backpressure: 25 bar (362 psi)	280 × 30 × 30 mm 0.47
	2000505	test pipe plug - Ø 35	clamping range: 35-40 mm construction: 1 sealing ring bypass: 8 mm max. backpressure: 20 bar (290 psi)	280 × 35 × 35 mm 0.50
	2000508	test pipe plug - Ø 40	clamping range: 40-45 mm construction: 1 sealing ring bypass: 8 mm max. backpressure: 20 bar (290 psi)	280 × 40 × 40 mm 0.54
	2000510	test pipe plug - Ø 50	clamping range: 50-55 mm construction: 1 sealing ring bypass: 8 mm max. backpressure: 20 bar (290 psi)	285 × 50 × 50 mm 0.64

	2000511	test pipe plug - Ø 60	clamping range: 60-65 mm construction: 1 sealing ring bypass: 8 mm max. backpressure: 15 bar (217 psi)	285 × 60 × 60 mm 0.76
	2000513	test pipe plug - Ø 65	clamping range: 65-70 mm construction: 1 sealing ring bypass: 8 mm max. backpressure: 15 bar (217 psi)	285 × 65 × 65 mm 0.81
	2000515	test pipe plug - Ø 70	clamping range: 70-75 mm construction: 1 sealing ring bypass: 8 mm max. backpressure: 10 bar (145 psi)	325 × 70 × 70 mm 0.92
	2000516	test pipe plug - Ø 75	clamping range: 75-80 mm construction: 1 sealing ring bypass: 8 mm max. backpressure: 10 bar (145 psi)	325 × 75 × 75 mm 1.00
	2000517	test pipe plug - Ø 80	clamping range: 75-95 mm construction: 2 sealing rings bypass: 8 mm max. backpressure: 6.0 bar (87 psi)	330 × 75 × 75 mm 1.59
	2000518	test pipe plug - Ø 90	clamping range: 85-105 mm construction: 2 sealing rings bypass: 8 mm max. backpressure: 5.5 bar (79.7 psi)	330 × 85 × 85 mm 1.80
	2000520	test pipe plug - Ø 100	clamping range: 95-115 mm construction: 2 sealing rings bypass: 8 mm max. backpressure: 5.0 bar (72.5 psi)	330 × 95 × 95 mm 1.94
	2000521	test pipe plug - Ø 110	clamping range: 105-125 mm construction: 2 sealing rings bypass: 8 mm max. backpressure: 4.8 bar (66.7 psi)	330 × 105 × 105 mm 2.00

	2000523	test pipe plug - Ø 125	clamping range: 120-140 mm construction: 2 sealing rings bypass: 8 mm max. backpressure: 4.5 bar (65.2 psi)	330 × 115 × 115 mm 2.15
	2000524	test pipe plug - Ø 130	clamping range: 120-140 mm construction: 2 sealing rings bypass: 8 mm max. backpressure: 4.2 bar (60.9 psi)	330 × 120 × 120 mm 2.20
	2000525	test pipe plug - Ø 140	clamping range: 135-155 mm construction: 2 sealing rings bypass: 8 mm max. backpressure: 4.2 bar (60.9 psi)	330 × 135 × 135 mm 2.70
	2000526	test pipe plug - Ø 150	clamping range: 145-165 mm construction: 2 sealing rings bypass: 8 mm max. backpressure: 4.0 bar (58 psi)	330 × 145 × 145 mm 2.90
	2000528	test pipe plug - Ø 160	clamping range: 155-175 mm construction: 2 sealing rings bypass: 8 mm max. backpressure: 3.8 bar (55.1 psi)	330 × 155 × 155 mm 3.15
	2000530	test pipe plug - Ø 175	clamping range: 170-190 mm construction: 2 sealing rings bypass: 8 mm max. backpressure: 3.5 bar (50.7 psi)	330 × 170 × 170 mm 3.70
	2000531	test pipe plug - Ø 190	clamping range: 175-200 mm construction: 2 sealing rings bypass: 8 mm max. backpressure: 3.2 bar (46.2 psi)	330 × 185 × 185 mm 4.23
	2000532	test pipe plug - Ø 200	clamping range: 195-215 mm construction: 2 sealing rings bypass: 12 mm max. backpressure: 3.0 bar (43.5 psi)	365 × 195 × 195 mm 4.90

	2000533	test pipe plug - Ø 210	clamping range: 205-225 mm construction: 2 sealing rings bypass: 12 mm max. backpressure: 2.8 bar (40.6 psi)	365 × 205 × 205 mm 5.00
	2000534	test pipe plug - Ø 225	clamping range: 220-240 mm construction: 2 sealing rings bypass: 12 mm max. backpressure: 2.6 bar (37.7 psi)	365 × 220 × 220 mm 5.15
	2000536	test pipe plug - Ø 235	clamping range: 230-250 mm construction: 2 sealing rings bypass: 12 mm max. backpressure: 2.5 bar (36.2 psi)	365 × 230 × 230 mm 5.25
	2000537	test pipe plug - Ø 250	clamping range: 245-265 mm construction: 2 sealing rings bypass: 12 mm max. backpressure: 2.5 bar (36.2 psi)	365 × 245 × 245 mm 6.40
	2000538	test pipe plug - Ø 260	clamping range: 255-275 mm construction: 2 sealing rings bypass: 12 mm max. backpressure: 2.4 bar (34.8 psi)	365 × 255 × 255 mm 7.00
	2000539	test pipe plug - Ø 275	clamping range: 270 - 290 mm construction: 2 sealing rings bypass: 12 mm max. backpressure: 2.0 bar (29 psi)	365 × 270 × 270 mm 7.50
	2000541	test pipe plug - Ø 300	clamping range: 295-315 mm construction: 2 sealing rings bypass: 12 mm max. backpressure: 2.0 bar (29 psi)	365 × 295 × 295 mm 8.50
	2000547	test pipe plug - Ø 350	clamping range: 345-365 mm construction: 2 sealing rings bypass: 30 mm max. backpressure: 1.5 bar (21.7 psi)	405 × 345 × 345 mm 10.0



2000563

test pipe plug - Ø 400

clamping range: 395 - 415 mm
construction: 2 sealing rings
bypass: 30 mm
max. backpressure: 1.0 bar (14.5 psi)

405 × 400 × 400 mm
 11.0



2000564

test pipe plug - Ø 450

clamping range: 445 - 465 mm
construction: 2 sealing rings
bypass: 30 mm
max. backpressure: 0.5 bar (7.25 psi)

405 × 450 × 450 mm
 12.5



2000565

test pipe plug - Ø 500

clamping range: 495 - 515 mm
construction: 2 sealing rings
bypass: 30 mm
max. backpressure: 0.5 bar (7.25 psi)

405 × 500 × 500 mm
 14.0



2000568

test pipe plug - Ø 600

clamping range: 595 - 615 mm
construction: 2 sealing rings
bypass: 30 mm
max. backpressure: 0.5 bar (7.25 psi)

405 × 600 × 600 mm
 16.5