

bendy packer

<https://ehle-hd.com/en/product/bendy-packer/>



Vetter's bendy packers have been specially developed for the rehabilitation of pipe bends and enable selective, trenchless resin-based repairs in curved or hard-to-reach pipe sections. Thanks to the special rubber with fabric reinforcement, the material does not buckle and expands optimally in bends, allowing pipe bends of up to 90° to be reliably rehabilitated.

The packers have a smooth outer surface to facilitate insertion and removal. Their design ensures that repairs are flush with the pipe wall, maintaining flow efficiency and long-term durability.

Features

- for the rehabilitation of offsets and pipe bends up to 90° in pipelines
- operating pressure: 3 bar
- standard length: 1250 mm
- max. repair lengths 930 mm
- made of special flexible rubber with embedded fabric
- smooth surface for even, swell-free repairs
- enables trenchless repairs in curved and offset pipe sections

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	V1492001500	bendy packer 30-50 / 1.25	work range: 30 - 50 mm Cylinder length: 1250 mm contact length: 1110 mm operating pressure: 3.0 bar (43.5 psi)	1350 × 24 × 24 mm 0.30
	V1492001600	bendy packer 50-70 / 1.25	work range: 50 - 70 mm Cylinder length: 1250 mm contact length: 930 mm operating pressure: 3.0 bar (43.5 psi)	1350 × 35 × 35 mm 0.60
	V1492001700	bendy packer 70-100 / 1.25	work range: 70 - 100 mm Cylinder length: 1250 mm contact length: 930 mm operating pressure: 3.0 bar (43.5 psi)	1350 × 55 × 55 mm 1.60
	V1492001800	bendy packer 100-125 / 1.25	work range: 100 - 125 m Cylinder length: 1250 mm contact length: 930 mm operating pressure: 3.0 bar (43.5 psi)	1350 × 55 × 55 mm 2.10
	V1492001900	bendy packer 125-150 / 1.25	work range: 125 - 150 mm Cylinder length: 1250 mm contact length: 930 mm operating pressure: 3.0 bar (43.5 psi)	1350 × 74 × 74 mm 2.40
	V1492002000	bendy packer 150-160 / 1.25	work range: 150 - 165 mm Cylinder length: 1250 mm contact length: 930 mm operating pressure: 3.0 bar (43.5 psi)	1350 × 74 × 74 mm 4.00
	V1492002100	bendy packer 170-220 / 1.25	work range: 170 - 220 mm Cylinder length: 1250 mm contact length: 930 mm operating pressure: 3.0 bar (43.5 psi)	1400 × 90 × 90 mm 9.50