

Bypass Flex-Packer 150-250

<https://ehle-hd.com/en/product/bypass-flex-packer-150-250/>



The **Flex-Packer DN 150 - 250 mm with bypass** enables the repair of pipe segments even in pipes with high water flow. No need for bypassing or pumps. The red, special extensible hose made of a soft rubber ensures very smooth contact surfaces and optimum transitions to the liner.

Available up to 10 m in length - special sizes on request.

Features

- light cast aluminium couplings
- with flexible passage Ø 38 mm
- optional snap on/off wheels for easy positioning of the packer
- raw dimension Ø 100 mm
- red, highly extensible hose (extension max. threefold outer diameter) with friction-resistant external sheet (smooth wrap, chequered fabric)
- Temperature range between -25°C and +60°C
- **max. 1.5 bar (36.2 psi) operation pressure**

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2002200	Bypass Flex-Packer 150-250 / 0.8 m	work range: 150 - 250 mm length: 800 mm contact length: approx 650 - 550 mm bypass: 38 mm operating pressure: 1.5 bar (21.8 psi)	800 × 100 × 100 mm 4.00
	2002201	Bypass Flex-Packer 150-250 / 1.0 m	work range: 150 - 250 mm length: 1,000 mm contact length: approx 850 - 750 mm bypass: 38 mm operating pressure: 1.5 bar (21.8 psi)	1000 × 100 × 100 mm 4.50
	2002202	Bypass Flex-Packer 150-250 / 1.2 m	work range: 150 - 250 mm length: 1,200 mm contact length: approx 1,050 - 900 mm bypass: 38 mm operating pressure: 1.5 bar (21.8 psi)	1200 × 100 × 100 mm 5.10
	2002204	Bypass Flex-Packer 150-250 / 1.5 m	work range: 150 - 250 mm length: 1,500 mm contact length: approx 1,350 - 1,200 mm bypass: 38 mm operating pressure: 1.5 bar (21.8 psi)	1500 × 100 × 100 mm 5.90
	2002206	Bypass Flex-Packer 150-250 / 2.0 m	work range: 150 - 250 mm length: 2,000 mm contact length: approx 1,850 - 1,700 mm bypass: 38 mm operating pressure: 1.5 bar (21.8 psi)	2000 × 100 × 100 mm 7.30
	2002208	Bypass Flex-Packer 150-250 / 2.5 m	work range: 150 - 250 mm length: 2,500 mm contact length: approx 2,350 - 2,250 mm bypass: 38 mm operating pressure: 1.5 bar (21.8 psi)	2500 × 100 × 100 mm 8.60
	2002210	Bypass Flex-Packer 150-250 / 3.0 m	work range: 150 - 250 mm length: 3,000 mm contact length: approx 2,850 - 2,700 mm bypass: 38 mm operating pressure: 1.5 bar (21.8 psi)	3000 × 100 × 100 mm 10.0



2002212

Bypass Flex-Packer 150-250 / 4.0 m

work range: 150 - 250 mm
length: 4,000 mm
contact length: approx 3,850 - 3,750 mm
bypass: 38 mm
operating pressure: 1.5 bar (21.8 psi)

4000 × 100 × 100 mm
12.7



2003114

snap on/off wheels - typ 1-4

150 × 100 × 100 mm
1.20