

Bypass Flex-Packer 450-1200

<https://ehle-hd.com/en/product/bypass-flex-packer-450-1200/>



The **Flex-Packer 450-1200 with bypass** consist of a single-layer rubber body and two metal heads with chassis (3x 120°), which ensure stable movement of the packer in the pipeline.

The packers are supplied with bypass so that the water can drain off during rehabilitation. Since the packers and the bypass are flexible, they can be easily installed in the damaged pipeline.

Features

- Stainless steel couplings with flexible bypass Ø 100 mm
- bypass with 4" inch female IG thread in the couplings
- including 3-point chassis (3x 120°) for easy positioning of the packer
- equipped with towing eye and air coupling
- ISO 9001 TÜV certified
- **max. operating pressure 1,0 bar**

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2003201	Bypass Flex-Packer 450-600 / 1.2 m	work range: 450 - 600 mm length: 1.100 mm bypass: 100 mm operating pressure: 1 bar (14,5 psi)	1340 x 360 x 360 mm 40.0
	2003202	Bypass Flex-Packer 450-600 / 1.7 m	work range: 450 - 600 mm length: 1.600 mm bypass: 100 mm operating pressure: 1 bar (14,5 psi)	1840 x 360 x 360 mm 45.0
	2003204	Bypass Flex-Packer 450-600 / 2.0 m	work range: 450 - 600 mm length: 2.000 mm bypass: 100 mm operating pressure: 1 bar (14,5 psi)	2240 x 360 x 360 mm 48
	2003205	Bypass Flex-Packer 450-600 / 2.7 m	work range: 450 - 600 mm length: 2.700 mm bypass: 100 mm operating pressure: 1 bar (14,5 psi)	2940 x 360 x 360 mm 55.0
	2003206	Bypass Flex-Packer 450-600 / 3.0 m	work range: 450 - 600 mm length: 3.000 mm bypass: 100 mm operating pressure: 1 bar (14,5 psi)	3240 x 360 x 360 mm 58.0
	2003210	Bypass Flex-Packer 600-800 / 1.4 m	work range: 600 - 800 mm length: 1.400 mm bypass: 100 mm operating pressure: 1 bar (14,5 psi)	1640 x 383 x 383 mm 61.0
	2003212	Bypass Flex-Packer 600-800 / 1.7 m	work range: 600 - 800 mm length: 1.700 mm bypass: 100 mm operating pressure: 1 bar (14,5 psi)	1940 x 383 x 383 mm 64.0

	2003214	Bypass Flex-Packer 600-800 / 2.0 m	work range: 600 - 800 mm length: 2.000 mm bypass: 100 mm operating pressure: 1 bar (14.5 psi)	2240 × 383 × 383 mm 67.0
	2003216	Bypass Flex-Packer 600-800 / 2.7 m	work range: 600 - 800 mm length: 2.700 mm bypass: 100 mm operating pressure: 1 bar (14.5 psi)	2940 × 383 × 383 mm 74.0
	2003218	Bypass Flex-Packer 600-800 / 3.0 m	work range: 600 - 800 mm length: 3.000 mm bypass: 100 mm operating pressure: 1 bar (14.5 psi)	3240 × 383 × 383 mm 77.0
	2003220	Bypass Flex-Packer 800-1000 / 1.8 m	work range: 800 - 1000 mm length: 1.800 mm bypass: 100 mm operating pressure: 1 bar (14.5 psi)	2040 × 550 × 550 mm 83.0
	2003230	Bypass Flex-Packer 1000-1200 / 2.2 m	work range: 1000 - 1200 mm length: 2.200 mm bypass: 100 mm operating pressure: 1 bar (14.5 psi)	2040 × 550 × 550 mm 90.0