

## Bypass Flex-Packer

<https://ehle-hd.com/en/product/bypass-flex-packer/>



The **Flex-Packer DN 150 - 250 mm with bypass** enables the repair of pipe segments even in pipes with high water flow. No need for bypassing or pumps. The red, special extensible hose made of a soft rubber ensures very smooth contact surfaces and optimum transitions to the liner.

**Available up to 10 m in length - special sizes on request.**

### Features

- light cast aluminium couplings
- with flexible passage Ø 38 mm
- optional snap on/off wheels for easy positioning of the packer
- raw dimension Ø 100 mm
- red, highly extensible hose (extension max. threefold outer diameter) with friction-resistant external sheet (smooth wrap, chequered fabric)
- Temperature range between -25°C and +60°C
- **max. 1.5 bar (36.2 psi) operation pressure**

## Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2002200	Bypass Flex-Packer 150-250 / 0.8 m	<b>work range:</b> 150 - 250 mm <b>length:</b> 800 mm <b>contact length:</b> approx 650 - 550 mm <b>bypass:</b> 38 mm <b>operating pressure:</b> 1.5 bar ( 21.8 psi)	800 × 100 × 100 mm 4.00
	2002201	Bypass Flex-Packer 150-250 / 1.0 m	<b>work range:</b> 150 - 250 mm <b>length:</b> 1,000 mm <b>contact length:</b> approx 850 - 750 mm <b>bypass:</b> 38 mm <b>operating pressure:</b> 1.5 bar ( 21.8 psi)	1000 × 100 × 100 mm 4.50
	2002202	Bypass Flex-Packer 150-250 / 1.2 m	<b>work range:</b> 150 - 250 mm <b>length:</b> 1,200 mm <b>contact length:</b> approx 1,050 - 900 mm <b>bypass:</b> 38 mm <b>operating pressure:</b> 1.5 bar ( 21.8 psi)	1200 × 100 × 100 mm 5.10
	2002204	Bypass Flex-Packer 150-250 / 1.5 m	<b>work range:</b> 150 - 250 mm <b>length:</b> 1,500 mm <b>contact length:</b> approx 1,350 - 1,200 mm <b>bypass:</b> 38 mm <b>operating pressure:</b> 1.5 bar ( 21.8 psi)	1500 × 100 × 100 mm 5.90
	2002206	Bypass Flex-Packer 150-250 / 2.0 m	<b>work range:</b> 150 - 250 mm <b>length:</b> 2,000 mm <b>contact length:</b> approx 1,850 - 1,700 mm <b>bypass:</b> 38 mm <b>operating pressure:</b> 1.5 bar ( 21.8 psi)	2000 × 100 × 100 mm 7.30
	2002208	Bypass Flex-Packer 150-250 / 2.5 m	<b>work range:</b> 150 - 250 mm <b>length:</b> 2,500 mm <b>contact length:</b> approx 2,350 - 2,250 mm <b>bypass:</b> 38 mm <b>operating pressure:</b> 1.5 bar ( 21.8 psi)	2500 × 100 × 100 mm 8.60
	2002210	Bypass Flex-Packer 150-250 / 3.0 m	<b>work range:</b> 150 - 250 mm <b>length:</b> 3,000 mm <b>contact length:</b> approx 2,850 - 2,700 mm <b>bypass:</b> 38 mm <b>operating pressure:</b> 1.5 bar ( 21.8 psi)	3000 × 100 × 100 mm 10.0

	2002212	Bypass Flex-Packer 150-250 / 4.0 m	<b>work range:</b> 150 - 250 mm <b>length:</b> 4,000 mm <b>contact length:</b> approx 3,850 - 3,750 mm <b>bypass:</b> 38 mm <b>operating pressure:</b> 1.5 bar ( 21.8 psi)	4000 × 100 × 100 mm 12.7
	2003100	Bypass Flex-Packer 250-400 / 1.2 m	<b>work range:</b> 250 - 400 mm <b>length:</b> 1,200 mm <b>contact length:</b> approx 950 - 850 mm <b>bypass:</b> 75 mm <b>operating pressure:</b> 1.5 bar ( 21.8 psi)	1200 × 205 × 205 mm 15.5
	2003102	Bypass Flex-Packer 250-400 / 1.5 m	<b>work range:</b> 250 - 400 mm <b>length:</b> 1,500 mm <b>contact length:</b> approx 1,200 - 1,100 mm <b>bypass:</b> 75 mm <b>operating pressure:</b> 1.5 bar ( 21.8 psi)	1500 × 205 × 205 mm 18.2
	2003104	Bypass Flex-Packer 250-400 / 2.0 m	<b>work range:</b> 250 - 400 mm <b>length:</b> 2,000 mm <b>contact length:</b> approx 1,700 - 1,600 mm <b>bypass:</b> 75 mm <b>operating pressure:</b> 1.5 bar ( 21.8 psi)	2000 × 205 × 205 mm 22.8
	2003106	Bypass Flex-Packer 250-400 / 2.5 m	<b>work range:</b> 250 - 400 mm <b>length:</b> 2,500 mm <b>contact length:</b> approx 2,200 - 2,100 mm <b>bypass:</b> 75 mm <b>operating pressure:</b> 1.5 bar ( 21.8 psi)	2500 × 205 × 205 mm 27.0
	2003108	Bypass Flex-Packer 250-400 / 3.0 m	<b>work range:</b> 250 - 400 mm <b>length:</b> 3,000 mm <b>contact length:</b> approx 2,700 - 2,600 mm <b>bypass:</b> 75 mm <b>operating pressure:</b> 1.5 bar ( 21.8 psi)	3000 × 205 × 205 mm 31.8
	2003110	Bypass Flex-Packer 250-400 / 4.0 m	<b>work range:</b> 250 - 400 mm <b>length:</b> 4,000 mm <b>contact length:</b> approx 3,700 - 3,600 mm <b>bypass:</b> 75 mm <b>operating pressure:</b> 1.5 bar ( 21.8 psi)	4000 × 205 × 205 mm 40.0
	2003114	snap on/off wheels - typ 1-4		150 × 100 × 100 mm 1.20