

## bypass pipe stoppers long - oil/chemicals

<https://ehle-hd.com/en/product/bypass-pipe-stoppers-long-oil-chemicals/>



The oil and chemical resistant **multi-size inflatable pipe stopper** in a long version enable tests of tank and chemical plants. They consist of special rubber with fabric insert. These are characterized by increased chemical resistance to mineral oil, heating oil, etc.

They serve three functions in one: sealing, testing with water or pressurized air, and bypassing / draining. The coreless cylinder and the rugged design allow adaption of the test cushions to the pipe surface and enable wide and flexible application ranges with excellent sealing properties.

### Features

- oil and chemicals resistant pipe stops to inspect industrial facilities and oil and petrol separators acc. to standard DIN 1999 T 100
- sewage bypassing in case of leaky sewers
- retention and controlled drainage of liquids
- leak tests acc. to standard DIN EN 1610 with pressurized air or water
- inspection of pipe sections
- resistant against weather and temperatures between -30°C and 80°C
- including floating bleeder hose
- ISO 9001 TÜV certified

**To avoid risk, we always recommend to use a support or a restrained joint acc. to DGUV Information 201-022 (previously, BGI 802)**

## Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2001429	oil bypass pipe stopper 70-150	<b>work range:</b> 70 - 150 mm <b>bypass:</b> 1" Geka <b>operating pressure:</b> 2.5 bar (36.2 psi) <b>max. backpressure:</b> 1.0 bar (14.5 psi)	420 × 67 × 67 mm 1.50
	2001430	oil bypass pipe stopper 100-200	<b>work range:</b> 100 - 200 mm <b>bypass:</b> 1" Geka <b>operating pressure:</b> 2.5 bar (36.2 psi) <b>max. backpressure:</b> 1.0 bar (14.5 psi)	600 × 96 × 96 mm 2.40
	2001431	oil bypass pipe stopper 150-300	<b>work range:</b> 150 - 300 mm <b>bypass:</b> 1" Geka <b>operating pressure:</b> 2.5 bar (36.2 psi) <b>max. backpressure:</b> 1.0 bar (14.5 psi)	640 × 135 × 135 mm 3.80
	2001432	oil bypass pipe stopper 200-400	<b>work range:</b> 200 - 400 mm <b>bypass:</b> 2" Storz-C <b>operating pressure:</b> 2.5 bar (36.2 psi) <b>max. backpressure:</b> 1.0 bar (14.5 psi)	670 × 190 × 190 mm 6.60
	2001433	oil bypass pipe stopper 300-600	<b>work range:</b> 300 - 600 mm <b>bypass:</b> 2x 2" Storz-C <b>operating pressure:</b> 1.5 bar ( 21.8 psi) <b>max. backpressure:</b> 0.5 bar (7.25 psi)	820 × 290 × 290 mm 13.4
	2001434	oil bypass pipe stopper 500-1000	<b>work range:</b> 500 - 1000 mm <b>bypass:</b> 2x 2" Storz-C <b>operating pressure:</b> 2.5 bar (36.2 psi) <b>max. backpressure:</b> 1.0 bar (14.5 psi)	1150 × 450 × 450 mm 39.0
	2001435	oil bypass pipe stopper 600-1200	<b>work range:</b> 600 - 1200 mm <b>bypass:</b> 2x 2" Storz-C <b>operating pressure:</b> 1.5 bar ( 21.8 psi) <b>max. backpressure:</b> 0.5 bar (7.25 psi)	1390 × 560 × 560 mm 58.0