

bypass pipe stoppers long - sewage

<https://ehle-hd.com/en/product/bypass-pipe-stoppers-long-sewage/>



The **multi-size inflatable pipe test stoppers with flexible bypass** they serve three functions in one: sealing, testing with water or pressurized air, and bypassing / draining. The coreless cylinder and the rugged design allow adaption of the test cushions to the pipe surface and enable wide and flexible application ranges with excellent sealing properties.

Features

- sewage bypassing in case of leaky sewers
- retention and controlled drainage of liquids
- leak tests acc. to standard DIN EN 1610 with pressurized air or water
- inspection of pipe sections
- resistant against weather and temperatures between -30°C and 80°C
- including floating bleeder hose
- ISO 9001 TÜV certified

To avoid risk, we always recommend to use a support or a restrained joint acc. to DGUV Information 201-022 (previously, BGI 802)

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2001200	bypass pipe stopper 70-150	work range: 70 - 150 mm bypass: 1" Geka operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	420 × 67 × 67 mm 1.50
	2001201	bypass pipe stopper 100-200	work range: 100 - 200 mm bypass: 1" Geka operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	600 × 96 × 96 mm 2.40
	2001203	bypass pipe stopper 150-300	work range: 150 - 300 mm bypass: 1" Geka operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	640 × 135 × 135 mm 3.80
	2001205	bypass pipe stopper 200-400	work range: 200 - 400 mm bypass: 2" Storz-C operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	660 × 190 × 190 mm 6.50
	2001208	bypass pipe stopper 300-600	work range: 300 - 600 mm bypass: 2x 2" Storz-C operating pressure: 1.5 bar (21.8 psi) max. backpressure: 0.5 bar (7.25 psi)	820 × 270 × 270 mm 13.4
	2001209	bypass pipe stopper 500-1000	work range: 500 - 1000 mm bypass: 2x 2" Storz-C operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	1150 × 450 × 450 mm 39.0
	2001210	bypass pipe stopper 600-1200	work range: 600 - 1200 mm bypass: 2x 2" Storz-C operating pressure: 1.5 bar (21.8 psi) max. backpressure: 0.5 bar (7.25 psi)	1390 × 560 × 560 mm 58.0



2001212

bypass pipe stopper 1000-1600

work range: 1000 - 1600 mm

bypass: 2x 2" Storz-C

operating pressure: 1 bar (14,5 psi)

max. backpressure: 0,5 bar (7,25 psi)

2000 x 850 x 850
mm

112.0