

## bypass pipe stoppers short - sewage

<https://ehle-hd.com/en/product/bypass-pipe-stoppers-short-sewage/>








The **short version of the multi-size inflatable pipe stopper with bypass** is particularly suitable in the house connection area and everywhere where the openings are too short or bends are present. They perform three functions in one: sealing, testing with water or air, and diverting/draining. The sealing pads are made of high quality rubber material with fabric insert. All metal parts are corrosion resistant.

### Features

- easy to use with standard couplings, even with short openings or directly in front of bends
- to bypass sewage of leaky sewers, for retention, and controlled drainage
- leak tests acc. to standard DIN EN 1610 with pressurized air or water
- resistant against weather and temperatures between -30°C and 80°C
- ISO 9001 TÜV certified

**To avoid risk, we always recommend to use a support or a restrained joint acc. to DGUV Information 201-022 (previously, BGI 802)**

## Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2001223	bypass pipe stopper short 50-70	<b>work range:</b> 50 - 70 mm <b>bypass:</b> 1/4" Geka <b>operating pressure:</b> 2.5 bar (36.2 psi) <b>max. backpressure:</b> 0.5 bar (7.25 psi)	190 × 46 × 46 mm 0.30
	2001220	bypass pipe stopper short 70-100	<b>work range:</b> 70 - 100 mm <b>bypass:</b> 1/2" Geka <b>operating pressure:</b> 2.5 bar (36.2 psi) <b>max. backpressure:</b> 0.5 bar (7.25 psi)	195 × 67 × 67 mm 0.40
	2001221	bypass pipe stopper short 100-150	<b>work range:</b> 100 - 150 mm <b>bypass:</b> 1/2" Geka <b>operating pressure:</b> 2.5 bar (36.2 psi) <b>max. backpressure:</b> 0.5 bar (7.25 psi)	195 × 90 × 90 mm 0.80
	2001222	bypass pipe stopper short 150-200	<b>work range:</b> 150 - 200 mm <b>bypass:</b> 1" Geka <b>operating pressure:</b> 2.5 bar (36.2 psi) <b>max. backpressure:</b> 0.5 bar (7.25 psi)	270 × 140 × 140 mm 2.00
	2001225	bypass pipe stopper short 200-250	<b>work range:</b> 200 - 250 mm <b>bypass:</b> 2" Storz-C <b>operating pressure:</b> 2.5 bar (36.2 psi) <b>max. backpressure:</b> 0.5 bar (7.25 psi)	320 × 180 × 180 mm 3.60
	2001228	bypass pipe stopper short 250-300	<b>work range:</b> 250 - 300 mm <b>bypass:</b> 2" Storz-C <b>operating pressure:</b> 2.5 bar (36.2 psi) <b>max. backpressure:</b> 0.5 bar (7.25 psi)	350 × 240 × 240 mm 5.90