

## FIX-Dicht quick-release stopper (Al)

<https://ehle-hd.com/en/product/fix-dicht-quick-release-stopper-ai/>



The **FIX-Dicht stopper** is a **safety quick-release plug of aluminum**. They are the rugged and long life version of the new stoppers to seal pipe ends fast, reliably, and safe. A pull rope attached makes it possible to remove the pipe stop safely from the manhole without the need to enter. This allows one man working alone with observance of the safety rules to prevent accidents and risks.

### Features

- the rugged design of aluminum and steel ensures a long service life
- riskless and economical manhole opening, no need to enter; simply attach a rope and pull (one man can work alone)
- used for leak tests acc. to DIN EN 1610 with pressurized air and water (including blank cover)
- for use in temperatures ranging from -40°C to 80°C

## Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2000231	FIX-Dicht stopper (Al) - Ø200	<b>use:</b> 175 mm (7") <b>clamping range:</b> 185-210 mm <b>bypass:</b> 1" <b>max. backpressure:</b> 0.5 bar (7.25 psi)	184 × 184 × 200 mm 3.06
	2000233	FIX-Dicht stopper (Al) - Ø225	<b>use:</b> 200 mm (8") <b>clamping range:</b> 205-235 mm <b>bypass:</b> 1" <b>max. backpressure:</b> 0.5 bar (7.25 psi)	207 × 207 × 200 mm 3.30
	2000235	FIX-Dicht stopper (Al) - Ø250	<b>use:</b> 225 mm (9") <b>clamping range:</b> 220-250 mm <b>bypass:</b> 1" <b>max. backpressure:</b> 0.5 bar (7.25 psi)	219 × 219 × 200 mm 3.52
	2000236	FIX-Dicht stopper (Al) - Ø270	<b>use:</b> 250 mm (10") <b>clamping range:</b> 240-270 mm <b>bypass:</b> 1" <b>max. backpressure:</b> 0.5 bar (7.25 psi)	243 × 243 × 200 mm 4.02
	2000238	FIX-Dicht stopper (Al) - Ø300	<b>clamping range:</b> 280-310 mm <b>bypass:</b> 1" <b>max. backpressure:</b> 0.5 bar (7.25 psi)	283 × 283 × 200 mm 5.14
	2000240	FIX-Dicht stopper (Al) - Ø315	<b>use:</b> 300 mm (12") <b>clamping range:</b> 298-323 mm <b>bypass:</b> 1" <b>max. backpressure:</b> 0.5 bar (7.25 psi)	297 × 297 × 200 mm 5.90
	2000241	FIX-Dicht stopper (Al) - Ø350	<b>use:</b> 350 mm (14") <b>clamping range:</b> 325-350 mm <b>bypass:</b> 1" <b>max. backpressure:</b> 0.3 bar (4.3 psi)	326 × 326 × 200 mm 6.24

	2000242	FIX-Dicht stopper (Al) - Ø375	<b>use:</b> 375 mm (15") <b>clamping range:</b> 352-382 mm <b>bypass:</b> 1" <b>max. backpressure:</b> 0.3 bar (4.3 psi)	355 × 355 × 200 mm 6.70
	2000243	FIX-Dicht stopper (Al) - Ø400	<b>clamping range:</b> 375-400 mm <b>bypass:</b> 1" <b>max. backpressure:</b> 0.3 bar (4.3 psi)	376 × 376 × 200 mm 7.62
	2000245	FIX-Dicht stopper (Al) - Ø420	<b>use:</b> 400 mm (16") <b>clamping range:</b> 400-425 mm <b>bypass:</b> 1" <b>max. backpressure:</b> 0.3 bar (4.3 psi)	402 × 402 × 200 mm 8.06
	2000247	FIX-Dicht stopper (Al) - Ø470	<b>use:</b> 450 mm (18") <b>clamping range:</b> 449-474 mm <b>bypass:</b> 1" <b>max. backpressure:</b> 0.3 bar (4.3 psi)	452 × 452 × 200 mm 9.56
	2000249	FIX-Dicht stopper (Al) - Ø500	<b>use:</b> 500 mm (20") <b>clamping range:</b> 500-521 mm <b>bypass:</b> 1" <b>max. backpressure:</b> 0.3 bar (4.3 psi)	499 × 499 × 200 mm 13.4