

FIX-Dicht quick-release stopper

<https://ehle-hd.com/en/product/fix-dicht-quick-release-stopper/>



The **FIX-Dicht stopper** is a **safety quick-release plug of plastic** and ensure a quick, reliable, and safe closure of pipe ends. The telescopic quick fasteners make installation and deinstallation of the stoppers safe and easy, no need to enter the manhole. Thanks to this remote control or a pull rope attached, one man can work alone and nevertheless obey the German safety regulations (BGR 126).

Features

- the corrosion resistant material (glass filled nylon) ensures a long service life
- Quick and economical application, since nobody needs to enter the manhole
- FIX-Dicht may be opened without risk. Use a rope or the telescopic quick fastener (extensible to 3.3 m)
- used for leak tests acc. to DIN EN 1610 with pressurized air and water (including blank cover)
- for use in temperatures ranging from -40°C to 80°C

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2000222	FIX-Dicht stopper (nylon) - Ø90	use: 90 mm (3 1/2") clamping range: 90-95 mm bypass: 1/2" max. backpressure: 0.5 bar (7.25 psi)	89 × 89 × 100 mm 0.24
	2000220	FIX-Dicht stopper (nylon) - Ø100	use: 100 mm (4") clamping range: 96-103 mm bypass: 1/2" max. backpressure: 0.5 bar (7.25 psi)	95 × 95 × 100 mm 0.24
	2000221	FIX-Dicht stopper (nylon) - Ø105	use: 105 mm (4") clamping range: 102-107 mm bypass: 1/2" max. backpressure: 0.5 bar (7.25 psi)	101 × 101 × 100 mm 0.24
	2000224	FIX-Dicht stopper (nylon) - Ø110	use: 110 mm (4") clamping range: 108-112 mm bypass: 1/2" max. backpressure: 0.5 bar (7.25 psi)	107 × 107 × 100 mm 0.30
	2000223	FIX-Dicht stopper (nylon) - Ø120	use: 120 mm (4 1/2") clamping range: 116-123 mm bypass: 1/2" max. backpressure: 0.5 bar (7.25 psi)	115 × 115 × 100 mm 0.36
	2000225	FIX-Dicht stopper (nylon) - Ø130	use: 125 mm (5") clamping range: 125-132 mm bypass: 1/2" max. backpressure: 0.5 bar (7.25 psi)	124 × 124 × 100 mm 0.40
	2000227	FIX-Dicht stopper (nylon) - Ø140	use: 140 mm (5 1/2") clamping range: 136-142 mm bypass: 1/2" max. backpressure: 0.5 bar (7.25 psi)	135 × 135 × 100 mm 0.44



2000226

FIX-Dicht stopper (nylon) - Ø145

use: 145 mm (5 3/4")
clamping range: 144-149 mm
bypass: 1/2"
max. backpressure: 0.5 bar (7.25 psi)

143 × 143 × 100 mm
 0.48



2000228

FIX-Dicht stopper (nylon) - Ø150

use: 150 mm (6")
clamping range: 147-153 mm
bypass: 1/2"
max. backpressure: 0.5 bar (7.25 psi)

148 × 148 × 100 mm
 0.48



2000229

FIX-Dicht stopper (nylon) - Ø160

use: 160 mm (6 1/2")
clamping range: 157-162 mm
bypass: 1/2"
max. backpressure: 0.5 bar (7.25 psi)

157 × 157 × 100 mm
 0.50