

Flex-Packer with bypass

<https://ehle-hd.com/en/product/flex-packer-with-bypass/>



Vetter's flexible rehabilitation packers with bypass allow pipe sections to be rehabilitated even in pipes with high water flow. There is no need for diversion or pumping. Thanks to their flexible design, the packers can be easily guided through a manhole opening and installed in the damaged pipe.

The packers have a chassis with a slight spring effect, which allows them to glide smoothly even over uneven surfaces. The wheels are positioned at an angle of 120 degrees. In addition, you can adjust the chassis individually to any pipe diameter.

Features

- Flex-Packer consists of a rubber jacket vulcanized onto two metal heads
- Flexible inner hose (bypass) allows water to drain during rehabilitation
 - Type 150 - 250 - bypass opening of 1" (25 mm)
 - Type 200 - 300 / 300 - 400 - bypass opening of 2" (50 mm)
 - From type 400 - 600 - bypass opening of 3" (75 mm)
- Adjustable 3-point chassis with 6 wheels for easy positioning of the packer
- Open safety coupling with locking pin prevents unintentional uncoupling
- Equipped with tow eye and air coupling
- Max. operating pressure depending on type 2.5 / 1.5 / 1.0 bar

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	V1491044801	Flex-Packer with bypass 200-300 / 1.0 m	work range: 200 - 300 mm length: 1.000 mm contact length: 690 - 590 mm bypass: 2" operating pressure: 1.5 bar (21.8 psi)	1130 × 170 × 170 mm 10
	V1491066500	Flex-Packer with bypass 200-300 / 1.5 m	work range: 200 - 300 mm length: 1.500 mm contact length: 1190 - 1090 mm bypass: 2" operating pressure: 1.5 bar (21.8 psi)	1630 × 170 × 170 mm 12.5
	V1491046301	Flex-Packer with bypass 200-300 / 2.0 m	work range: 200 - 300 mm length: 2.000 mm contact length: 1690 - 1590 mm bypass: 2" operating pressure: 1.5 bar (21.8 psi)	2130 × 170 × 170 mm 15
	V1491066600	Flex-Packer with bypass 200-300 / 2.5 m	work range: 200 - 300 mm length: 2.500 mm contact length: 2190 - 2090 mm bypass: 2" operating pressure: 1.5 bar (21.8 psi)	2630 × 170 × 170 mm 17.5
	V1491046401	Flex-Packer with bypass 200-300 / 3.0 m	work range: 200 - 300 mm length: 3.000 mm contact length: 2690 - 2590 mm bypass: 2" operating pressure: 1.5 bar (21.8 psi)	3130 × 170 × 170 mm 20
	V1491044901	Flex-Packer with bypass 300-400 / 1.0 m	work range: 300 - 400 mm length: 1.000 mm bypass: 2" operating pressure: 1.5 bar (21.8 psi)	1170 × 230 × 230 mm 13.2
	V1491066700	Flex-Packer with bypass 300-400 / 1.5 m	work range: 300 - 400 mm length: 1.500 mm contact length: 1160 - 1060 mm bypass: 2" operating pressure: 1.5 bar (21.8 psi)	1670 × 230 × 230 mm 16.5

	V1491046601	Flex-Packer with bypass 300-400 / 2.0 m	work range: 300 - 400 mm length: 2.000 mm contact length: 1660 - 1560 mm bypass: 2" operating pressure: 1.5 bar (21.8 psi)	2170 × 230 × 230 mm 19.4
	V1491066800	Flex-Packer with bypass 300-400 / 2.5 m	work range: 300 - 400 mm length: 2.500 mm contact length: 2160 - 2060 mm bypass: 2" operating pressure: 1.5 bar (21.8 psi)	2670 × 230 × 230 mm 23.0
	V1491046701	Flex-Packer with bypass 300-400 / 3.0 m	work range: 300 - 400 mm length: 3.000 mm contact length: 2660 - 2560 mm bypass: 2" operating pressure: 1.5 bar (21.8 psi)	3170 × 230 × 230 mm 26.0
	V1491045701	Flex-Packer with bypass 400-600 / 1.5 m	length: 1.500 mm contact length: 1240 - 980 mm bypass: 3" operating pressure: 1.5 bar (21.8 psi) work range: 400 - 600 mm	1670 × 350 × 350 mm 26.1
	V1491059500	Flex-Packer with bypass 400-600 / 2.0 m	work range: 400 - 600 mm length: 2.000 mm contact length: 1450 - 1400 mm bypass: 3" operating pressure: 1.5 bar (21.8 psi)	2170 × 350 × 350 mm 29.0
	V1491059001	Flex-Packer with bypass 600-800 / 1.5 m	work range: 600 - 800 mm length: 1.500 mm contact length: 900 - 700 mm bypass: 3" operating pressure: 1 bar (14.5 psi)	1670 × 400 × 400 mm 29.0
	V1491058601	Flex-Packer with bypass 800-1000 / 1.5 m	work range: 800 - 1000 mm length: 1.500 mm contact length: 760 - 520 mm bypass: 3" operating pressure: 1 bar (14.5 psi)	1670 × 550 × 550 mm 50.0
	V1491059600	Flex-Packer with bypass 1000-1200 / 2.2 m	work range: 1000 - 1200 mm length: 2.200 mm contact length: 1200 - 1000 mm bypass: 3" operating pressure: 1 bar (14.5 psi)	2370 × 550 × 550 mm 73.0