

Flexible packer 100-150

<https://ehle-hd.com/en/product/flexible-packer-100-150/>



The **Flex-Packers DN 100-150 mm** were especially designed for short and long liners in sewer rehabilitation. For us, lightweight construction and universal application were key. The red special extensible hose made of a soft rubber ensures very smooth contact surfaces and optimum transitions between liner and the pipe to be rehabilitated.

Available up to 10 m in length - special sizes on request.

Features

- the rounded, lightweight aluminum cast couplings ensure an easy and trouble free installation; equipped with drawbar eye and air coupling
- raw dimension Ø 75 mm
- red, highly extensible hose (extension max. threefold outer diameter) with friction-resistant external sheet (smooth wrap, chequered fabric)
- Temperature range between -25°C and +60°C
- **max. 2.5 bar (36.2 psi) operation pressure**

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2002150	Flexible Packer 100-150 / 0.4 m	length: 400 mm contact length: approx 300 - 200 mm operating pressure: 2.5 bar (36.2 psi)	400 × 75 × 75 mm 2.30
	2002152	Flexible Packer 100-150 / 0.8 m	length: 800 mm contact length: approx 700 - 600 mm operating pressure: 2.5 bar (36.2 psi)	800 × 75 × 75 mm 2.80
	2002154	Flexible Packer 100-150 / 1.0 m	length: 1,000 mm contact length: approx 850 - 700 mm operating pressure: 2.5 bar (36.2 psi)	1000 × 75 × 75 mm 3.10
	2002156	Flexible Packer 100-150 / 1.2 m	length: 1,200 mm contact length: approx 1,050 - 900 mm operating pressure: 2.5 bar (36.2 psi)	1200 × 75 × 75 mm 3.30
	2002158	Flexible Packer 100-150 / 1.5 m	length: 1,500 mm contact length: approx 1,350 - 1,200 mm operating pressure: 2.5 bar (36.2 psi)	1500 × 75 × 75 mm 3.60
	2002160	Flexible Packer 100-150 / 2.0 m	length: 2,000 mm contact length: approx 1,800 - 1,700 mm operating pressure: 2.5 bar (36.2 psi)	2000 × 75 × 75 mm 4.20
	2002162	Flexible Packer 100-150 / 2.5 m	length: 2,500 mm contact length: approx 2,300 - 2,200 mm operating pressure: 2.5 bar (36.2 psi)	2500 × 75 × 75 mm 4.80



2002164

Flexible Packer 100-150 / 3.0 m

length: 3,000 mm
contact length: approx 2,800 - 2,700 mm
operating pressure: 2.5 bar (36.2 psi)

3000 × 75 × 75 mm
 5.40



2002165

Flexible Packer 100-150 / 4.0 m

length: 4,000 mm
contact length: approx 3,800 - 3,700 mm
operating pressure: 2.5 bar (36.2 psi)

4000 × 75 × 75 mm
 6.60



2002166

Flexible Packer 100-150 / 5.0 m

length: 5,000 mm
contact length: approx 4,800 - 4,700 mm
operating pressure: 2.5 bar (36.2 psi)

5000 × 75 × 75 mm
 7.80