

Flexible packer without bypass

<https://ehle-hd.com/en/product/flexible-packer-without-bypass/>



Our **Flex-Packers** were especially designed for short and long liners in sewer rehabilitation. For us, lightweight construction and universal application were key. The red special extensible hose made of a soft rubber ensures very smooth contact surfaces and optimum transitions between liner and the pipe to be rehabilitated.

Special sizes on request

Features

- the lightweight aluminum couplings ensure an easy and trouble free installation; equipped with drawbar eye and air coupling
- red, highly extensible hose (extension max. threefold outer diameter) with friction-resistant external sheet (smooth wrap, chequered fabric)
- Temperature range between -25°C and $+60^{\circ}\text{C}$
- **max. 2.5 bar (36.2 psi) operation pressure**

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2002121	Flex-Packer 80-125 / 0.6 m	work range: 80 - 125 mm length: 600 mm contact length: approx 500 - 400 mm operating pressure: 2.5 bar (36.2 psi)	600 × 65 × 65 mm 1.30
	2002122	Flex-Packer 80-125 / 0.8 m	work range: 80 - 125 mm length: 800 mm contact length: approx 700 - 600 mm operating pressure: 2.5 bar (36.2 psi)	800 × 65 × 65 mm 1.50
	2002123	Flex-Packer 80-125 / 1.0 m	work range: 80 - 125 mm length: 1,000 mm contact length: approx 850 - 700 mm operating pressure: 2.5 bar (36.2 psi)	1000 × 65 × 65 mm 1.60
	2002120	Flex-Packer 80-125 / 1.2 m	work range: 80 - 125 mm length: 1,200 mm contact length: approx 1,050 - 900 mm operating pressure: 2.5 bar (36.2 psi)	1200 × 65 × 65 mm 1.70
	2002125	Flex-Packer 80-125 / 1.5 m	work range: 80 - 125 mm length: 1,500 mm contact length: approx 1,350 - 1,200 mm operating pressure: 2.5 bar (36.2 psi)	1500 × 65 × 65 mm 2.20
	2002127	Flex-Packer 80-125 / 2.0 m	work range: 80 - 125 mm length: 2,000 mm contact length: approx 1,850 - 1,700 mm operating pressure: 2.5 bar (36.2 psi)	2000 × 65 × 65 mm 2.70
	2002129	Flex-Packer 80-125 / 3.0 m	work range: 80 - 125 mm length: 3,000 mm contact length: approx 2,850 - 2,700 mm operating pressure: 2.5 bar (36.2 psi)	3000 × 65 × 65 mm 3.80

	2002150	Flexible Packer 100-150 / 0.4 m	work range: 100 - 150 mm length: 400 mm contact length: approx 300 - 200 mm operating pressure: 2.5 bar (36.2 psi)	400 × 75 × 75 mm 2.30
	2002152	Flexible Packer 100-150 / 0.8 m	work range: 100 - 150 mm length: 800 mm contact length: approx 700 - 600 mm operating pressure: 2.5 bar (36.2 psi)	800 × 75 × 75 mm 2.80
	2002154	Flexible Packer 100-150 / 1.0 m	work range: 100 - 150 mm length: 1,000 mm contact length: approx 850 - 700 mm operating pressure: 2.5 bar (36.2 psi)	1000 × 75 × 75 mm 3.10
	2002156	Flexible Packer 100-150 / 1.2 m	work range: 100 - 150 mm length: 1,200 mm contact length: approx 1,050 - 900 mm operating pressure: 2.5 bar (36.2 psi)	1200 × 75 × 75 mm 3.30
	2002158	Flexible Packer 100-150 / 1.5 m	work range: 100 - 150 mm length: 1,500 mm contact length: approx 1,350 - 1,200 mm operating pressure: 2.5 bar (36.2 psi)	1500 × 75 × 75 mm 3.60
	2002160	Flexible Packer 100-150 / 2.0 m	work range: 100 - 150 mm length: 2,000 mm contact length: approx 1,800 - 1,700 mm operating pressure: 2.5 bar (36.2 psi)	2000 × 75 × 75 mm 4.20
	2002162	Flexible Packer 100-150 / 2.5 m	work range: 100 - 150 mm length: 2,500 mm contact length: approx 2,300 - 2,200 mm operating pressure: 2.5 bar (36.2 psi)	2500 × 75 × 75 mm 4.80
	2002164	Flexible Packer 100-150 / 3.0 m	work range: 100 - 150 mm length: 3,000 mm contact length: approx 2,800 - 2,700 mm operating pressure: 2.5 bar (36.2 psi)	3000 × 75 × 75 mm 5.40

	2002165	Flexible Packer 100-150 / 4.0 m	work range: 100 - 150 mm length: 4,000 mm contact length: approx 3,800 - 3,700 mm operating pressure: 2.5 bar (36.2 psi)	4000 × 75 × 75 mm 6.60
	2002166	Flexible Packer 100-150 / 5.0 m	work range: 100 - 150 mm length: 5,000 mm contact length: approx 4,800 - 4,700 mm operating pressure: 2.5 bar (36.2 psi)	5000 × 75 × 75 mm 7.80
	2002180	Flexible Packer pointed 150-250 / 0.8 m	work range: 100 - 150 mm length: 800 mm contact length: approx 650 - 550 mm operating pressure: 1.5 bar (21.8 psi)	800 × 100 × 100 mm 3.00
	2002181	Flexible Packer pointed 150-250 / 1.0 m	work range: 100 - 150 mm length: 1,000 mm contact length: approx 850 - 750 mm operating pressure: 1.5 bar (21.8 psi)	1000 × 100 × 100 mm 3.30
	2002182	Flexible Packer pointed 150-250 / 1.2 m	work range: 100 - 150 mm length: 1,200 mm contact length: approx 1,050 - 900 mm operating pressure: 1.5 bar (21.8 psi)	1200 × 100 × 100 mm 3.70
	2002183	Flexible Packer pointed 150-250 / 1.5 m	work range: 100 - 150 mm length: 1,500 mm contact length: approx 1,350 - 1,200 mm operating pressure: 1.5 bar (21.8 psi)	1500 × 100 × 100 mm 4.20
	2002185	Flexible Packer pointed 150-250 / 2.0 m	work range: 100 - 150 mm length: 2,000 mm contact length: approx 1,850 - 1,700 mm operating pressure: 1.5 bar (21.8 psi)	2000 × 100 × 100 mm 5.00
	2002188	Flexible Packer pointed 150-250 / 2.5 m	work range: 100 - 150 mm length: 2,500 mm contact length: approx 2,350 - 2,250 mm operating pressure: 1.5 bar (21.8 psi)	2500 × 100 × 100 mm 6.00



2002189

Flexible Packer pointed 150-250 /
3.0 m

work range: 100 - 150 mm
length: 3,000 mm
contact length: approx 2,850 -
2,700 mm
operating pressure: 1.5 bar (21.8
psi)

3000 × 100 × 100
mm
6.70



2002190

Flexible Packer pointed 150-250 /
4.0 m

work range: 100 - 150 mm
length: 4,000 mm
contact length: approx 3,850 -
3,750 mm
operating pressure: 1.5 bar (21.8
psi)

4000 × 100 × 100
mm
8.50