

Guide hoses

<https://ehle-hd.com/en/product/guide-hoses/>







The clamping jaw system is used to put the guide hose on the stay bolts and to fix it with grub screws to reduce cable vibrations.



Features

- Spiral plastic hose in different lengths
- for RAK and RIS cable machines
- can be mounted directly on the respective machine

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	14200222	RAK-39 guide hose - 2.1 m long	length: 2.1 m	2100 x 80 x 80 mm 1.00
	14200232	RAK-40 guide hose - 4.0 m long	length: 4 m	4000 x 80 x 80 mm 2.50
	14200242	RAK-41 guide hose - 0.5m long	length: 0.5 m	500 x 80 x 80 mm 0.80
	14200243	RAK-41 guide hose - 4.0 m long	length: 4 m	4000 x 80 x 80 mm 2.50
	14200143	RIS-Power 22/16 guide hose	length: 4.2 m	4200 x 80 x 80 mm 2.60
	14200156	RIS-16 guide hose	length: 4.2 m	4200 x 80 x 80 mm 2.60
	14200153	RIS-22 guide hose	length: 4.2 m	4200 x 80 x 80 mm 2.60

14200165

RIS-32 guide hose

length: 4.2 m

4200 × 80 × 80 mm
2.60

