

hose trolley

<https://ehle-hd.com/en/product/hose-trolley/>



Our **mobile hose trolley** for 3/8" high-pressure hoses with a length of 40 or 60 m and is the ideal accessory for mobile cleaning applications where the location cannot be reached directly by vehicle – for example, in basements, underground garages, or on large construction sites.

The hose trolley significantly expands your operating radius while allowing you to remain flexible and mobile. In combination with a camera flush nozzle, it enables improved propulsion for push camera systems, even with many bends, while ensuring effective pipe cleaning.

Features

- 1/2" hose connection, high-pressure swivel joint, shut-off ball valve, and nozzle holders
- 3/8" flushing hose in lengths of 40 m and 60 m
- galvanized steel tube construction with a low center of gravity for exceptional stability
- robust reel lock prevents unwanted unwinding during transport
- XL heavy-duty wheels – extra large for safe rolling on gravel, lawns, or construction sites
- very compact, handy, and particularly easy to transport
- can be used as an extension for cleaning small pipes – even with many bends

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	S102238	Haspel-Rolli with 60 m hose 3/8"	connection: 1/2" female thread length: 60 m operating pressure: max. 250 bar	565 × 529 × 976 mm 33.3
	S102237	Haspel-Rolli with 40 m hose 3/8"	connection: 1/2" female thread length: 40 m operating pressure: max. 250 bar	565 × 529 × 976 mm 28.0
	S102239	Haspel-Rolli without hose	connection: 1/2" female thread length: (-) operating pressure: max. 250 bar	565 × 529 × 976 mm 12.8
	19916030	3/8" push-camera nozzle	connection: 3/8" female thread application from: 80 - 200 mm water supply: from 25 lpm thrust nozzles: 4x M6 thrust jet angle: 25°	55 × 40 × 40 mm 0.37
	1100064	3/8" KR tube nozzle with front jet	connection: 3/8" female thread application from: 50 - 150 mm water supply: from 35 lpm thrust nozzles: 6x with bore thrust jet angle: 25° front nozzles: 1x with bore front jet angle: 0°	35 × 25 × 25 mm 0.07
	1100096	3/8" ball nozzle	connection: 3/8" female thread application from: 40 - 110 mm water supply: from 20 lpm thrust nozzles: 4x with bore thrust jet angle: 25° front nozzles: (-)	25 × 25 × 25 mm 0.06