

Inflatable pipe stoppers long - oil/chemicals

<https://ehle-hd.com/en/product/inflatable-pipe-stoppers-long-oil-chemicals/>



The **multi-size inflatable pipe stopper** in long version is resistant for oil/chemicals resistant and made of of special rubber (SR) with embedded fabric. Their benefits are the higher resistance against chemicals, mineral oil, fuel oil etc..

The pipe stopper designed for quick and reliable sealing or retention of sewers, pipes, and drainages. They are recommended mainly for repairs, maintenance, failures, and leak inspections with water or pressurized air acc. to standard DIN EN 1610 performed at new buried or rehabilitated pipes.

Features

- Pipe stops resistant against oil and chemicals applied in industrial facilities and in case of chemicals spilled; also useful for oil and gasoline separators tests acc. to standard DIN 1999 T 100
- to seal and shut-off pipes in case of repairs, maintenance, or failures
- applied for damaged pipes, flood, sewer inspection, sewer cleaning, maintenance or repair
- Leak tests acc. to standard DIN EN 1610 of new buried or rehabilitated pipes
- Resistant against weather and temperatures between -30°C and 80°C
- ISO 9001 TÜV certified

To avoid risk, we always recommend to use a support or a restrained joint acc. to DGUV Information 201-022 (previously, BGI 802)

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2001420	oil pipe stopper 50-100	work range: 50 - 100 mm operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	390 × 47 × 47 mm 0.50
	2001421	oil pipe stopper 70-150	work range: 70 - 150 mm operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	365 × 67 × 67 mm 0.50
	2001422	oil pipe stopper 100-200	work range: 100 - 200 mm operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	555 × 96 × 96 mm 1.20
	2001423	oil pipe stopper 150-300	work range: 150 - 300 mm operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	595 × 135 × 135 mm 2.10
	2001425	oil pipe stopper 200-400	work range: 200 - 400 mm operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	625 × 190 × 190 mm 3.90
	2001426	oil pipe stopper 300-600	work range: 300 - 600 mm operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	775 × 270 × 270 mm 7.60
	2001427	oil pipe stopper 500-1000	work range: 500 - 1000 mm operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	1120 × 450 × 450 mm 25.0



2001428

oil pipe stopper 600-1200

work range: 600 - 1200 mm

operating pressure: 1.5 bar (21.8
psi)

max. backpressure: 0.5 bar (7.25 psi)

1360 x 560 x 560

mm
38