

pipe stoppers long - sewage

<https://ehle-hd.com/en/product/inflatable-pipe-stoppers-long/>



The **multi-size inflatable pipe stopper** in long version is designed for quick and reliable sealing or retention of sewers, pipes, and drainages. They are recommended mainly for repairs, maintenance, failures, and leak inspections with water or pressurized air acc. to standard DIN EN 1610 performed at new buried or rehabilitated pipes.

Features

- to seal and shut-off pipes in case of repairs, maintenance, or failures
- applied for damaged pipes, flood, sewer inspection, sewer cleaning, maintenance or repair
- Leak tests acc. to standard DIN EN 1610 of new buried or rehabilitated pipes
- Resistant against weather and temperatures between -30°C and 80°C
- ISO 9001 TÜV certified

To avoid risk, we always recommend to use a support or a restrained joint acc. to DGUV Information 201-022 (previously, BGI 802)

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2001100	pipe stopper 18-35	work range: 18 - 35 mm operating pressure: 2 bar (29 psi) max. backpressure: 1.0 bar (14.5 psi)	100 × 18 × 18 mm 0.20
	2001101	pipe stopper 35-50	work range: 35 - 50 mm operating pressure: 2 bar (29 psi) max. backpressure: 1.0 bar (14.5 psi)	105 × 32 × 32 mm 0.25
	2001102	pipe stopper 50-70	work range: 50 - 70 mm operating pressure: 2 bar (29 psi) max. backpressure: 1.0 bar (14.5 psi)	115 × 47 × 47 mm 0.30
	2001106	pipe stopper 40-70	work range: 40 - 70 mm operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	270 × 38 × 38 mm 0.30
	2001103	pipe stopper 50-100	work range: 50 - 100 mm operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	390 × 47 × 47 mm 0.50
	2001105	pipe stopper 70-150	work range: 70 - 150 mm operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	365 × 67 × 67 mm 0.50
	2001107	pipe stopper 100-200	work range: 100 - 200 mm operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	555 × 96 × 96 mm 1.20

	2001108	pipe stopper 150-300	work range: 150 - 300 mm operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	595 × 135 × 135 mm 2.10
	2001109	pipe stopper 200-400	work range: 200 - 400 mm operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	625 × 190 × 190 mm 3.90
	2001110	pipe stopper 300-600	work range: 300 - 600 mm operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	775 × 270 × 270 mm 7.60
	2001112	pipe stopper 500-1000	work range: 500 - 1000 mm operating pressure: 2.5 bar (36.2 psi) max. backpressure: 1.0 bar (14.5 psi)	1120 × 450 × 450 mm 25.0
	2001115	pipe stopper 600-1200	work range: 600 - 1200 mm operating pressure: 1.5 bar (21.8 psi) max. backpressure: 0.5 bar (7.25 psi)	1360 × 560 × 560 mm 38
	2001117	pipe stopper 1000-1600	work range: 1000 - 1600 mm operating pressure: 1 bar (14.5 psi) max. backpressure: 0.5 bar (7.25 psi)	1970 × 850 × 850 mm 95