DATASHEET

ehle

Jetcam 4.0

https://ehle-hd.com/en/product/jetcam-4-0/



The new **JETCAM 4.0 jetting nozzle camera** is based on the proven JETCAM 40 Pro and has been enhanced with new technologies such as wireless tablet control, data enrollment in the app, 512 Hz location sensor, longer battery life and inductive charging.

It is used for cleaning and inspecting municipal and private pipe systems. The small jetting camera can be used from DN 50 to 300 mm and is characterized by its compactness, maneuverability and precision. Angled inlet and outlet connections, as are common in basements, are no problem for the maneuverable JETCAM, which can handle angles of up to 90° without any problems. With high pressure, the jetting nozzle camera removes dirt, blockages and can even be equipped with a pre-jet nozzle.

Cleaning, inspecting, bending and documenting in a single operation.

Features

- is easy to use
- Pipes from DN 50 DN 300
- house connection pipes and main pipes
- Branches from the main channel to the side channel
- Preparation for inspection, damage repair and leak test
- direct control of the cleaning success and control of the damage repair
- hard-to-reach areas
- Foldable and rollable, it can be taken wherever it is needed.
- It fits in almost every vehicle and can be operated by one person with a weight of 45 kg.

Wlan control unit:

- Live image on tablet via SewerLinkApp
- Meter counter, compliant with standards
- OnScreen Text
- Data Recording
- Locating 512 Hz



DATASHEET



Stainless steel reel:

- 1/2" connection BSP female thread
- Water filter
- Needle valve
- Pressure gauge
- Tablet holder
- Hand crank with gear ratio
- Reel brake prevents unintentional unwinding
- Carrying handles

Complete set consists of:

- Stainless steel reel
- camera head 32 / 50 mm, wide angle lens, mugel, 5 bar waterproof
- Steering piece with cleaning nozzle
- high pressure hose, electronically assembled, 60 meters, 1/2" or 3/8
- High performance Lithium Ion battery with 99 Wh (> 7h runtime) and charger
- Accessories

Optional:

- Rotation nozzle (available for 3/8" and 1/2" version)
- Vibration nozzle (only available for 1/2 variant)
- Pre-jet nozzle with skid
- changeable nozzle set for JetCam

For an optimal working use:

- approx. 40l/min., 100 150 bar with 3/8" hose, on reel
- approx. 60l/min., 130 150 bar with 1/2" hose, at the reel

page 2



DATASHEET



Attributes

nage	SKU	Productname	Attributes	LxWxH & Weight
	S7000310	Jetcam 4.0 - 3/8" hose	HP-hose: 3/8" with 60 m length work range: from 50 - 300 mm 45" bends: from 50 mm 90" bends: from 70 mm type: complete set connection: 1/2" female thread	560 × 590 × 830 mm 45.0
	S7000311	Jetcam 4.0 - 1/2" hose	HP-hose: 1/2" with 60 m length work range: from 70 - 300 mm 45" bends: from 70 mm 90" bends: from 100 mm type: complete set connection: 1/2" female thread	560 × 590 × 830 mm 45.0
0	7000312	Changeable nozzle set JetCam 1/2*	connection : 1/2* female thread type : accessories	100 × 100 × 80 mm 1.10
١	7000360	Frontjet nozzle with skid	front nozzles: 1x M4	60 × 50 × 50 mm 1.10
(tile)	7000373	3/8' Rotating nozzle with steering	connection: 3/8" female thread type: accessories	500 × 50 × 50 mm 1.10
(II))	7000370	1/2" Rotating nozzle with steering	connection : 1/2* female thread type : accessories	500 × 50 × 50 mm 1.10
Su ?	7000374	1/2" Vibration nozzle with steering	connection : 1/2* female thread type : accessories	500 × 50 × 50 mm 1.10

page 3

