

K-40 Sink machine

<https://ehle-hd.com/en/product/k-40-sink-machine/>



The **K-40** sits flat on the floor or countertop and also tips onto its back for easy access to sink drains and bathtubs full of water. It practically eliminates job site cleanup thanks to the patented guide hose two-way AUTOFEED® control. It completely contains the rotating cable and eliminates any waste water splashing or spraying.

The Model K-40 Sink Machine is ideal for cleaning small secondary drain lines.

- 1/4" (6 mm) cables best for 3/4" to 1 1/2" (20 mm to 40 mm) lines.
- 5/16" (8 mm) cables best for 3/4" to 1 1/2" (20 mm to 40 mm) lines.
- 3/8" (10 mm) cables best for 1 1/4" to 2 1/2" (40 mm to 75 mm) lines.

Features

- 175-watt induction motor quietly delivers enough torque to clear even the toughest blockages.
- Premium-quality, compression-wound inner core cable combines strength and flexibility to resist kinking.
- Two-piece "twist lock" drum housing will not dent or corrode and allows easy access to the inner drum and cable.
- Special inner drum design virtually eliminates cable flip-over inside the drum and drum leakage.
- Two-way AUTOFEED control advances and retrieves the drain cleaning cable with a simple push of a lever keeping you and the work area clean.
- Includes RIDGID® drain cleaning gloves and operator's manual.

Technical data:

- **Pipe diameter:** from 20 - 75 mm
- **Standard cable length:** 10.7 m
- **Spirals / Working length:**
 - 6 mm cables up to 10 m
 - 8 mm cables up to 15 m
 - 10 mm cables up to 10 m
- **Motor power:** 175 W Induction motor

page 1








- **Voltage:** 230 V / 50 Hz
- **Speed:** 270 rpm
- **Weight:** 15 kg
- **Further features:** 2-way feed AUTOFEED® & guide hose

K-40 sink machine kit includes:

- K-40 Hand drum machine
- 8 mm cable / 10.7 m long
- guide tube
- foot switch

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	R71742	K-40 sink machine	cable typ: 6 mm 8 mm 10 mm	230 × 110 × 140 mm 15.00
	14200110	Replacement Cable Ø 6 / 5 m	cable typ: 6 mm length: 5 m material strength: 2.0 mm	200 × 200 × 30 mm 0.60
	14200111	Replacement Cable Ø 6 / 7.5 m	cable typ: 6 mm length: 7.5 m material strength: 2.0 mm	200 × 200 × 30 mm 0.90
	14200112	Replacement Cable Ø 8 / 7.5 m	cable typ: 8 mm length: 7.5 m material strength: 2.0 mm	200 × 200 × 40 mm 2.20
	14200115	Replacement Cable Ø 8 / 10 m	cable typ: 8 mm length: 10 m material strength: 2.0 mm	200 × 200 × 40 mm 2.30
	14200114	Replacement Cable with inner core Ø 8 / 7.5 m (Kopie)	cable typ: 8 mm length: 7.5 m material strength: 2.0 mm	200 × 200 × 40 mm 2.30
	14200116	Replacement Cable with inner core Ø 8 / 10 m	cable typ: 8 mm length: 10 m material strength: 2.0 mm	200 × 200 × 40 mm 2.40

	<p>14200117</p>	<p>Replacement Cable Ø 10 / 7,5 m</p>	<p>cable typ: 10 mm length: 7,5 m material strength: 2,5 mm</p>	<p>200 × 200 × 40 mm 2.20</p>
	<p>14200120</p>	<p>Replacement Cable Ø 10 / 10 m</p>	<p>cable typ: 10 mm length: 10 m material strength: 2,5 mm</p>	<p>200 × 200 × 40 mm 3.70</p>
	<p>14200119</p>	<p>Replacement Cable with 16 T-coupling Ø 10 / 7,5 m</p>	<p>cable typ: 10 mm length: 7,5 m material strength: 2,5 mm</p>	<p>200 × 200 × 40 mm 2.80</p>
	<p>14200122</p>	<p>Replacement Cable with 16 T-coupling Ø 10 / 10 m</p>	<p>cable typ: 10 mm length: 10 m material strength: 2,5 mm</p>	<p>200 × 200 × 40 mm 4.00</p>
	<p>14200118</p>	<p>Replacement Cable with core Ø 10 / 7,5 m</p>	<p>cable typ: 10 mm length: 7,5 m material strength: 2,5 mm</p>	<p>200 × 200 × 40 mm 2.80</p>
	<p>14200121</p>	<p>Replacement Cable with core Ø 10 / 10 m</p>	<p>cable typ: 10 mm length: 10 m material strength: 2,5 mm</p>	<p>200 × 200 × 40 mm 3.50</p>
	<p>14200123</p>	<p>Replacement Cable with 16 T-coupling and core Ø 10 / 10 m</p>	<p>cable typ: 10 mm length: 7,5 m material strength: 2,5 mm</p>	<p>200 × 200 × 40 mm 4.50</p>