

## K-45 Sink machine

<https://ehle-hd.com/en/product/k-45-sink-machine/>



The **hand operated motor cable unit K-45AF-5** is very handy and designed for mobile troubleshooting in kitchen and bath. It may be used in drains of diameter 20 – 75 mm. The continuously variable drive with thrust control produces the forward and reverse thrust of the cable through optional CW/CCW rotation of the drive. The container drum is made of rugged, glass fiber reinforced nylon and accepts cables of 8 mm and 10 mm diameter (quick changeover possible).

### Features

- Excellent for small line cleaning 20 - 75 mm.
- Opens clogged lavatory, sink lines, urinals and tub or shower drains.
- Advanced two-way AUTOFEED® control keeps hands and work area clean – advances & retrieves cable with push of a lever.
- Manual version has a slide-action chuck for quick locking/releasing of cable (Not available in Europe).
- Lightweight, easy-to-use, no setup required.
- Variable speed power unit rotates cable 0-600 RPMs.
- **Two-piece twist lock canister with interchangeable inner drum** - Makes cable change-out simple; easy to match the right cable for the job.
- Inner drum prevents water leaks and greatly reduces cable flip-over inside the drum.
- Drums won't rust or dent-ever.
- Drum Capacity: 50' of 5/16" (15 m of 8 mm) or 35' of 3/8" (11 m of 10 mm).
- Includes RIDGID® drain cleaning gloves and operator's manual.
- Approved by CSA to CSA and UL Standards (115V only).

### Technical data:



- **Pipe diameter** from 20 - 75 mm
- **Spirals / Working length:**
  - 6 mm spiral up to 10 m
  - 8 mm spiral up to 15 m
  - 10 mm spiral up to 10 m








- **Motor:** 400 W Input power
- **Voltage:** 230 V / 50 Hz
- **Speed:** stepless, clockwise / anticlockwise rotation
- **Weight:** 6 kg
- **Dimensions (LxWxH):** 620 x 240 x 300 mm

## Set K-45AF-5 sink machine includes:

- 8 mm cable with bulb auger - 7.5 m long
- 10 mm cable with T-coupling - 10 m long
- transport case
- Tools for cable 10 mm:
  - 1x articulated bulb auger
  - 1x grease fork
  - 1x bulb auger
  - 1x round spade cutter
  - 1x pointed Spade cutter
  - 1x mitt
  - 1x cable release wrench

## Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	R36043	K-45 sink machine - complete kit	<b>cable typ:</b> 10 mm 6 mm 8 mm	620 x 240 x 300 mm 15.40
	14200110	Replacement Cable Ø 6 / 5 m	<b>cable typ:</b> 6 mm <b>length:</b> 5 m <b>material strength:</b> 2.0 mm	200 x 200 x 30 mm 0.60
	14200111	Replacement Cable Ø 6 / 7.5 m	<b>cable typ:</b> 6 mm <b>length:</b> 7.5 m <b>material strength:</b> 2.0 mm	200 x 200 x 30 mm 0.90
	14200112	Replacement Cable Ø 8 / 7.5 m	<b>cable typ:</b> 8 mm <b>length:</b> 7.5 m <b>material strength:</b> 2.0 mm	200 x 200 x 40 mm 2.20
	14200115	Replacement Cable Ø 8 / 10 m	<b>cable typ:</b> 8 mm <b>length:</b> 10 m <b>material strength:</b> 2.0 mm	200 x 200 x 40 mm 2.30
	14200114	Replacement Cable with inner core Ø 8 / 7.5 m (Kopie)	<b>cable typ:</b> 8 mm <b>length:</b> 7.5 m <b>material strength:</b> 2.0 mm	200 x 200 x 40 mm 2.30
	14200116	Replacement Cable with inner core Ø 8 / 10 m	<b>cable typ:</b> 8 mm <b>length:</b> 10 m <b>material strength:</b> 2.0 mm	200 x 200 x 40 mm 2.40

	<p>14200117</p>	<p>Replacement Cable Ø 10 / 7,5 m</p>	<p><b>cable typ:</b> 10 mm <b>length:</b> 7,5 m <b>material strength:</b> 2,5 mm</p>	<p>200 × 200 × 40 mm 2.20</p>
	<p>14200120</p>	<p>Replacement Cable Ø 10 / 10 m</p>	<p><b>cable typ:</b> 10 mm <b>length:</b> 10 m <b>material strength:</b> 2,5 mm</p>	<p>200 × 200 × 40 mm 3.70</p>
	<p>14200119</p>	<p>Replacement Cable with 16 T-coupling Ø 10 / 7,5 m</p>	<p><b>cable typ:</b> 10 mm <b>length:</b> 7,5 m <b>material strength:</b> 2,5 mm</p>	<p>200 × 200 × 40 mm 2.80</p>
	<p>14200122</p>	<p>Replacement Cable with 16 T-coupling Ø 10 / 10 m</p>	<p><b>cable typ:</b> 10 mm <b>length:</b> 10 m <b>material strength:</b> 2,5 mm</p>	<p>200 × 200 × 40 mm 4.00</p>
	<p>14200118</p>	<p>Replacement Cable with core Ø 10 / 7,5 m</p>	<p><b>cable typ:</b> 10 mm <b>length:</b> 7,5 m <b>material strength:</b> 2,5 mm</p>	<p>200 × 200 × 40 mm 2.80</p>
	<p>14200121</p>	<p>Replacement Cable with core Ø 10 / 10 m</p>	<p><b>cable typ:</b> 10 mm <b>length:</b> 10 m <b>material strength:</b> 2,5 mm</p>	<p>200 × 200 × 40 mm 3.50</p>
	<p>14200123</p>	<p>Replacement Cable with 16 T-coupling and core Ø 10 / 10 m</p>	<p><b>cable typ:</b> 10 mm <b>length:</b> 7,5 m <b>material strength:</b> 2,5 mm</p>	<p>200 × 200 × 40 mm 4.50</p>