

K9-102 FlexShaft drain cleaning machine

<https://ehle-hd.com/en/product/k9-102-flexshaft-drain-cleaning-machine/>



The new FlexShaft drums are compact and highly efficient machines that offer complete high-speed pipe cleaning from 32 - 50 mm (1 1/4" to 2"). FlexShaft can also be operated when an inspection camera is located in the pipe so that the inside of the pipe can continue to be inspected during cleaning.

Features

- Applications: sinks, tubs, urinals, showers
- Type of blockage: Deposits and grease impurities
- The chain centrifuges expand for complete pipe cleaning
- With FlexShaft drums, you can leave your inspection camera in the pipeline during application
- Quick set-up and packing, quick cleaning and wireless, convenient operation provide additional time savings
- A comprehensive range of chain centrifuges and accessories is available
- The unit is driven by a cordless screwdriver with slip clutch (not included in delivery)







Technical data:

- Pipe diameter from 32 - 50 mm (1 1/4" - 2")
- Cable length: 15.2 m (50")
- Cable diameter (without sheathing): 6 mm
- Cable diameter (with sheathing): 9.5 mm
- Speed: min rpm RPM - max. 2500 rpm
- Drill connection: 5/16" Hex (8mm)
- weight: 13.4 kg
- Operating temperature: -6°C to 60°C

K9-102 Complete set consisting of:

- FlexShaft drum including 15.2 m cable
- Chain spinner with 1 smooth chain
- Chain centrifuge with 2 smooth chains
- FlexShaft Oil (120 ml)
- PVC Attachments
- Tool and tool bag

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	R64268	Kg-102 FlexShaft - drain cleaning machine kit	work range: 32 - 50 mm length: 15 m flex shaft cable typ: 6 mm	488 × 191 × 562 mm 13.4
	R64293	FlexShaft chain knocker (6 mm) - 1 chain	work range: 32 - 50 mm construction: single chain	80 × 40 × 20 mm 0.08
	R64298	FlexShaft chain knocker (6 mm) - 2 chains	work range: 50 mm construction: double chains	80 × 40 × 20 mm 0.10
	R64283	FlexShaft chain knocker (6 mm) - 1 chain with carbide tips	work range: 32 - 50 mm construction: single chain	80 × 40 × 20 mm 0.08
	R64288	FlexShaft chain knocker (6 mm) - 2 chains with carbide tips	work range: 50 mm construction: double chains	80 × 40 × 20 mm 0.10
	R64338	FlexShaft Lubricant	content: 8oz (238 ml)	50 × 50 × 150 mm 0.36