

Long packers without wheels

<https://ehle-hd.com/en/product/long-packers-without-wheels/>



Our **long packer** without wheels and without bypass are used in the pipe and sewer rehabilitation for rehabilitation work where no sewage flow is required. The flexible design allows a rehabilitation length of 100 cm to 400 cm, for pipe diameters from 200 to 800 mm.

The rehabilitation packers consist of a rubber hose with aluminium heads at both ends. The aluminium heads have a safety quick coupling and a towing eye on each side.

Features


- rubber body and two metal heads
- compressed air connection on both sides with safety quick coupling
- towing eyes on both sides
- ISO 9001 TÜV certified

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2005200	Longpacker 200-300 / 1.0 m	work range: 200 - 300 mm length: 1.000 mm operating pressure: 1.5 bar (21.8 psi)	1100 × 150 × 150 mm 3.70
	2005201	Longpacker 200-300 / 1.5 m	work range: 200 - 300 mm length: 1.500 mm operating pressure: 1.5 bar (21.8 psi)	1600 × 150 × 150 mm 4.80
	2005202	Longpacker 200-300 / 2.0 m	work range: 200 - 300 mm length: 2.000 mm operating pressure: 1.5 bar (21.8 psi)	2100 × 150 × 150 mm 5.90
	2005203	Longpacker 200-300 / 2.5 m	work range: 200 - 300 mm length: 2.500 mm operating pressure: 1.5 bar (21.8 psi)	2600 × 150 × 150 mm 7.00
	2005204	Longpacker 200-300 / 3.0 m	work range: 200 - 300 mm length: 3.000 mm operating pressure: 1.5 bar (21.8 psi)	3100 × 150 × 150 mm 8.10
	2005205	Longpacker 200-300 / 3.5 m	work range: 200 - 300 mm length: 3.500 mm operating pressure: 1.5 bar (21.8 psi)	3600 × 150 × 150 mm 9.10
	2005206	Longpacker 200-300 / 4.0 m	work range: 200 - 300 mm length: 4.000 mm operating pressure: 1.5 bar (21.8 psi)	4100 × 150 × 150 mm 10.2

	2005207	Longpacker 300-400 / 1.0 m	work range: 300 - 400 mm length: 1.000 mm operating pressure: 1.5 bar (21.8 psi)	1100 × 240 × 240 mm 6.50
	2005208	Longpacker 300-400 / 1.5 m	work range: 300 - 400 mm length: 1.500 mm operating pressure: 1.5 bar (21.8 psi)	1600 × 240 × 240 mm 8.50
	2005209	Longpacker 300-400 / 2.0 m	work range: 300 - 400 mm length: 2.000 mm operating pressure: 1.5 bar (21.8 psi)	2100 × 240 × 240 mm 10.6
	2005210	Longpacker 300-400 / 2.5 m	work range: 300 - 400 mm length: 2.500 mm operating pressure: 1.5 bar (21.8 psi)	2600 × 240 × 240 mm 12.7
	2005211	Longpacker 300-400 / 3.0 m	work range: 300 - 400 mm length: 3.000 mm operating pressure: 1.5 bar (21.8 psi)	3100 × 240 × 240 mm 14.7
	2005212	Longpacker 300-400 / 3.5 m	work range: 300 - 400 mm length: 3.500 mm operating pressure: 1.5 bar (21.8 psi)	3600 × 240 × 240 mm 16.7
	2005213	Longpacker 300-400 / 4.0 m	work range: 300 - 400 mm length: 4.000 mm operating pressure: 1.5 bar (21.8 psi)	4100 × 240 × 240 mm 18.8
	2005214	Longpacker 400-500 / 1.5 m	work range: 400 - 500 mm length: 1.500 mm operating pressure: 1 bar (14.5 psi)	1600 × 340 × 340 mm 16.0

	2005215	Longpacker 400-500 / 2.0 m	work range: 400 - 500 mm length: 2.000 mm operating pressure: 1 bar (14,5 psi)	2100 × 340 × 340 mm 21.0
	2005216	Longpacker 400-500 / 2.5 m	work range: 400 - 500 mm length: 2.500 mm operating pressure: 1 bar (14,5 psi)	2600 × 340 × 340 mm 24.0
	2005217	Longpacker 400-500 / 3.0 m	work range: 400 - 500 mm length: 3.000 mm operating pressure: 1 bar (14,5 psi)	3100 × 340 × 340 mm 26.5
	2005218	Longpacker 400-500 / 3.5 m	work range: 400 - 500 mm length: 3.500 mm operating pressure: 1 bar (14,5 psi)	3600 × 340 × 340 mm 29.0
	2005219	Longpacker 400-500 / 4.0 m	work range: 400 - 500 mm length: 4.000 mm operating pressure: 1 bar (14,5 psi)	4100 × 340 × 340 mm 32.0
	2005220	Longpacker 500-600 / 1.5 m	work range: 500 - 600 mm length: 1.500 mm operating pressure: 1 bar (14,5 psi)	2100 × 430 × 430 mm 21.0
	2005221	Longpacker 500-600 / 2.0 m	work range: 500 - 600 mm length: 2.000 mm operating pressure: 1 bar (14,5 psi)	2600 × 430 × 430 mm 28.3
	2005222	Longpacker 500-600 / 2.5 m	work range: 500 - 600 mm length: 2.500 mm operating pressure: 1 bar (14,5 psi)	2600 × 430 × 430 mm 31.8

	2005223	Longpacker 500-600 / 3,0 m	work range: 500 - 600 mm length: 3,000 mm operating pressure: 1 bar (14,5 psi)	3100 × 430 × 430 mm 35,4
	2005224	Longpacker 500-600 / 3,5 m	work range: 500 - 600 mm length: 3,500 mm operating pressure: 1 bar (14,5 psi)	3600 × 430 × 430 mm 39,0
	2005225	Longpacker 500-600 / 4,0 m	work range: 500 - 600 mm length: 4,000 mm operating pressure: 1 bar (14,5 psi)	4100 × 430 × 430 mm 42,5
	2005226	Longpacker 600-800 / 1,5 m	work range: 600 - 800 mm length: 1,500 mm operating pressure: 0,6 bar (8,70 psi)	1600 × 510 × 510 mm 42,0
	2005227	Longpacker 600-800 / 2,0 m	work range: 600 - 800 mm length: 2,000 mm operating pressure: 0,6 bar (8,70 psi)	2100 × 510 × 510 mm 49,0
	2005228	Longpacker 600-800 / 2,5 m	work range: 600 - 800 mm length: 2,500 mm operating pressure: 0,6 bar (8,70 psi)	2600 × 510 × 510 mm 52,5
	2005229	Longpacker 600-800 / 3,0 m	work range: 600 - 800 mm length: 3,000 mm operating pressure: 0,6 bar (8,70 psi)	3100 × 510 × 510 mm 56,0
	2005230	Longpacker 600-800 / 3,5 m	work range: 600 - 800 mm length: 3,500 mm operating pressure: 0,6 bar (8,70 psi)	3600 × 510 × 510 mm 59,5

2005231

Longpacker 600-800 / 4.0 m

work range: 600 - 800 mm
length: 4.000 mm
operating pressure: 0.6 bar (8.70
psi)

4100 × 510 × 510 mm
63.0

