

M12 SIC020 Push camera system

<https://ehle-hd.com/en/product/m12-sic020-push-camera-system/>



The **M12 SIC020 cordless sewer inspection system** was designed for narrow sanitary pipes, traps and bends. It offers optimum illumination in pipes from 32 - 75 mm. The system can connect wirelessly via WiFi to a tablet, smartphone or additional monitor and is controlled via the free Pipeline Inspection app.

The robust 16 mm stainless steel camera head delivers high-resolution HD video, while the flexible 6.5 mm push cable (20 m long) masters multiple 90° bends. With an integrated metre counter, controllable locating probe (512 / 640 Hz) and exchangeable 12V batteries, the inspection system offers maximum flexibility - ideal for emergency service operations in sanitary and kitchen pipes.

Features

- The modular MILWAUKEE® camera system allows users to select the camera drum that best suits their specific requirements on site
- The new self-levelling 16 mm full HD camera guarantees first-class images even in low light conditions
- 20 m long, 6.5 mm ultra-flexible push cable, that runs through multiple 32 mm 90 degree bends
- Integrated smart hub with a USB port for data storage
- Wi-Fi functionality allows the sewer inspection camera to transfer data via USB-A, USB-C and wirelessly
- With its small footprint, the camera can be easily stored in any van and can be used in the tightest of spaces
- Built-in probe for easy localisation: 512 and 640 Hz for use with all common locating devices
- Can be used with M18, M12 Monitor and the Pipeline Inspection App
- Fully enclosed coils for better protection against dirt
- Top handle for easier transport
- Rubber stand for placing the coil on the back
- 12 LEDs for better illumination of drain pipes
- Best LED geometry for optimum illumination of 32 mm - 75 mm drains

Technical specifications

- Camera head: 16 mm, self-levelling

page 1



- Cable length: 20 m
- Cable diameter: 6.5 mm
- Line capacity: 32 - 75 mm
- HD resolution: 1920 x 1080 px
- Positioning transmitter: 512 Hz, 640 Hz
- Metre counter: yes
- Protection class: IP67

Scope of delivery

- M12 SIC020 push camera system
- no batteries and charger included
- supplied in a box

App für Smartphone / Tablet über **Google Play Store** bzw. **Apple App Store** kostenlos zum Download

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	M4933498231	M12 SLC020-0 - push camera	type: without battery and charger application from: 32 - 75 mm length: 20 m push rod: Ø 6,5 mm camera: 16 mm Self Leveling Axial Camera	610 × 370 × 430 mm 9.50
	M4933471414	M18 SIM-0 - Wireless Monitor	type: without battery and charger	100 × 250 × 250 mm 2.4