

## mini bypass pipe stoppers

<https://ehle-hd.com/en/product/mini-bypass-pipe-stoppers/>



The **mini inflatable pipe plugs with bypass** are the ideal solution for leak testing, inspections, maintenance and cleaning work on pipes. Thanks to their integrated bypass, they enable secure sealing as well as testing and drainage of the medium – in pipes up to DN 300.

Their compact design makes the pipe closures particularly suitable for tight installation situations, short openings and pipe runs with bends.

### Features

- integrated bypass – for testing, sealing or draining pipes up to DN 300
- versatile application – suitable for leak tests, inspections, maintenance and cleaning work
- easy handling even with short openings or before bends
- short design – ideal for house connection pipes and tight installation situations
- better handling thanks to the extension of the filling valve
- high flexibility and bendability for use in pipes with short openings or bends
- high elasticity for reliable sealing of different pipe diameters
- counterpressure up to 1 bar enables versatile testing and sealing applications (counterpressure up to 10 m water column possible)
- easy handling thanks to compact and robust design
- leak tests in accordance with DIN EN 1610 with air or water
- high quality control – each shut-off bladder undergoes testing after production and receives a test seal
- Made in Germany

**On request, we can also supply the short test pipe caps with a Storz D coupling instead of the GEKA coupling. Simply leave a short message in the information field of your enquiry. For safety reasons, we generally recommend the use of a shoring device or a push-out protection device in accordance with DGUV Information 201-022 (formerly BGI 802).**

## Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	V1492000900	mini bypass pipe stoppers - PDK3,5/7	<b>work range:</b> 35 - 70 mm <b>bypass:</b> 6 mm <b>Cylinder length:</b> 200 mm <b>operating pressure:</b> 2.5 bar (36.2 psi) <b>max. backpressure:</b> 1.0 bar (14.5 psi)	250 × 32 × 32 mm 0.40
	V1492001000	mini bypass pipe stoppers - PDK7/10	<b>work range:</b> 70 - 100 mm <b>bypass:</b> 1/4" <b>Cylinder length:</b> 150 mm <b>operating pressure:</b> 2.5 bar (36.2 psi) <b>max. backpressure:</b> 1.0 bar (14.5 psi)	200 × 65 × 65 mm 0.45
	V1492001100	mini bypass pipe stoppers - PDK10/15	<b>work range:</b> 100 - 150 mm <b>bypass:</b> 1/2" <b>Cylinder length:</b> 150 mm <b>operating pressure:</b> 2.5 bar (36.2 psi) <b>max. backpressure:</b> 1.0 bar (14.5 psi)	200 × 85 × 85 mm 0.60
	V1492001200	mini bypass pipe stoppers - PDK15/20	<b>work range:</b> 150 - 200 mm <b>bypass:</b> 1" <b>Cylinder length:</b> 200 mm <b>operating pressure:</b> 2.5 bar (36.2 psi) <b>max. backpressure:</b> 1.0 bar (14.5 psi)	250 × 135 × 135 mm 1.50