

Multi-Packers 100-200

<https://ehle-hd.com/en/product/multi-packers-100-200/>



The **Multi-Packers 100 - 200** consist of very hard-wearing and thick-walled rubber material with 2 additional cord inlays, thus this packer is very robust and has a very excellent expansion behaviour, so that it has a wider range of application compared to the normal rehabilitation packers. The pressing length ranges from 600 mm to 4,000 mm.

Features

- short tapered vulcanized rubber stoppers, for an ideal pushing behaviour even through bends
- are highly flexible and yet dimensionally stable
- also suitable for strong pipe offsets
- equipped with a safety coupling and a drawbar eye
- ISO 9001 TÜV certified

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2005180	Multi-Packer 100-200 / 0.6	work range: 100 - 200 mm length: 600 mm operating pressure: 2.5 bar (36.2 psi)	680 × 68 × 68 mm 1.90
	2005181	Multi-Packer 100-200 / 1.0	work range: 100 - 200 mm length: 1,000 mm operating pressure: 2.5 bar (36.2 psi)	1080 × 68 × 68 mm 2.90
	2005182	Multi-Packer 100-200 / 1.5	work range: 100 - 200 mm length: 1,500 mm operating pressure: 2.5 bar (36.2 psi)	1580 × 68 × 68 mm 4.10
	2005183	Multi-Packer 100-200 / 2.0	work range: 100 - 200 mm length: 2,000 mm operating pressure: 2.5 bar (36.2 psi)	2080 × 68 × 68 mm 5.30
	2005184	Multi-Packer 100-200 / 2.5	work range: 100 - 200 mm length: 2,500 mm operating pressure: 2.5 bar (36.2 psi)	2580 × 68 × 68 mm 6.55
	2005185	Multi-Packer 100-200 / 3.0	work range: 100 - 200 mm length: 3,000 mm operating pressure: 2.5 bar (36.2 psi)	3080 × 68 × 68 mm 7.80
	2005186	Multi-Packer 100-200 / 3.5	work range: 100 - 200 mm length: 3,500 mm operating pressure: 2.5 bar (36.2 psi)	3580 × 68 × 68 mm 9.00

2005187

Multi-Packer 100-200 / 4.0

work range: 100 - 200 mm

length: 4.000 mm

operating pressure: 2.5 bar (36.2 psi)

4080 × 68 × 68 mm
10.2

