

Multi-Packers 50-125

<https://ehle-hd.com/en/product/multi-packers-50-125/>



The **Multi-Packers 50 - 125** consist of very hard-wearing and thick-walled rubber material with 2 additional cord inlays, thus this packer is very robust and has a very excellent expansion behaviour, so that it has a wider range of application compared to the normal rehabilitation packers. The pressing length ranges from 600 mm to 4,000 mm.

Features

- short tapered vulcanized rubber stoppers, for an ideal pushing behaviour even through bends
- are highly flexible and yet dimensionally stable
- also suitable for strong pipe offsets
- equipped with a safety coupling and a drawbar eye
- ISO 9001 TÜV certified

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2005160	Multi-Packer 50-125 / 0.6	work range: 50 - 125 mm length: 600 mm operating pressure: 2.5 bar (36.2 psi)	680 × 40 × 40 mm 0.95
	2005161	Multi-Packer 50-125 / 1.0	work range: 50 - 125 mm length: 1,000 mm operating pressure: 2.5 bar (36.2 psi)	1080 × 40 × 40 mm 1.30
	2005162	Multi-Packer 50-125 / 1.5	work range: 50 - 125 mm length: 1,500 mm operating pressure: 2.5 bar (36.2 psi)	1580 × 40 × 40 mm 1.80
	2005163	Multi-Packer 50-125 / 2.0	work range: 50 - 125 mm length: 2,000 mm operating pressure: 2.5 bar (36.2 psi)	2080 × 40 × 40 mm 2.25
	2005164	Multi-Packer 50-125 / 2.5	work range: 50 - 125 mm length: 2,500 mm operating pressure: 2.5 bar (36.2 psi)	2580 × 40 × 40 mm 2.70
	2005165	Multi-Packer 50-125 / 3.0	work range: 50 - 125 mm length: 3,000 mm operating pressure: 2.5 bar (36.2 psi)	3080 × 40 × 40 mm 3.15
	2005166	Multi-Packer 50-125 / 3.5	work range: 50 - 125 mm length: 3,500 mm operating pressure: 2.5 bar (36.2 psi)	3580 × 40 × 40 mm 3.65

2005167

Multi-Packer 50-125 / 4.0

work range: 50 - 125 mm

length: 4.000 mm

operating pressure: 2.5 bar (36.2 psi)

4080 × 40 × 40 mm
410

