

Picote Midi Cleaner

<https://ehle-hd.com/en/product/picote-midi-cleaner/>



The powerful **Midi Cleaner** machines use the stronger yet flexible 10 mm flexshaft. This makes the machines ideal for cleaning, descaling and removing roots in DN50 - 150 mm pipes as well as for milling/preparing DN50 - 100 pipes. In combination with a Picote Brush Coating™ pump, they can also be used for coating DN50 - 200 pipes.

Features

- Cleaning / descaling: DN 50 - 150 mm
- Milling / rehabilitation preparation: DN 50 - 100 mm
- Picote Brush Coating™: DN 50 - 200 mm
- The Midi Cleaner's flexible 10 mm shaft makes it easy to navigate through several 90° bends, even in DN50 pipes
- Infinitely adjustable speed and high torque
- Parallel camera inspection possible
- Universal 10 mm Flexshaft shaft, Reach 23 m + 10 m extension
- High-speed drain cleaning Unblocking and root removal
- with foot pedal for comfortable working with 2 hands
- The standard safety equipment with electronic safety clutch, protective shaft casing and emergency stop protects you and your equipment
- A stable frame construction protects the technology and increases the service life.
- Suitable for Picote Brush Coating™ in combination with coating pump

Technical data:

- **Pipe diameter:** from 50 - 150 mm
- **cable length:** 23 m + 10 m extension
- **flexshaft:** 10 mm
- **flexshaft protective layer:** regular
- **Rotation speed:** 500 - 1500 min⁻¹

- **Output:** 1500 W
- **Voltage:** 230 V, 16A
- **IP protection class:** 54
- **Weight with battery:** 65 kg

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	P3551031000	Midi Cleaner - 230 V	work range: 50 - 150 mm shaft typ: 10 mm length: 23 m + 10 m Power: 230 volts brands: Picote	1122 x 712 x 466 mm 65