

## Picote Super Midi Miller

<https://ehle-hd.com/en/product/picote-super-midi-miller/>



The **Super Midi Miller** closes the gap between the capabilities of the Mini and Maxi Miller and impresses with the additional power of a larger 12 mm shaft.

The machine is suitable for cleaning, descaling, root removal as well as milling and repair work in pipes from DN70 to DN150. With a reach of 20 meters, which can be extended to up to 30 meters with a shaft extension, it offers a high degree of flexibility on the construction site. The use of a thinner shaft casing significantly increases maneuverability - ideal for use in bends and angled pipe runs.

The Super Midi Miller can also be combined with the Picote Maxi Coating pump to reliably coat pipes in the DN70 to DN200 range.

### Features

- Cleaning / descaling: DN 70 - 150 mm
- Milling / rehabilitation preparation: DN 70 - 150 mm
- Picote Brush Coating™: DN 70 - 200 mm
- Parallel camera inspection possible
- 12 mm shaft with thinner shaft casing for greater maneuverability in pipes with bends
- Range 20 m + 10 m extension
- Infinitely adjustable speed and high torque
- High-speed pipe cleaning for unclogging and root removal
- With foot pedal for comfortable working with 2 hands
- The standard safety equipment with electronic safety clutch, protective shaft casing and emergency stop protects you and your equipment
- A sturdy frame construction protects the technology and increases the service life.
- Suitable for Picote Brush Coating™ in combination with coating pump

### Technical data:

- **Pipe diameter:** from 70 - 150 mm
- **cable length:** 20 m + 10 m extension
- **flexshaft:** 12 mm
- **flexshaft protective layer:** thin

page 1

- **Rotation speed:** 500 - 1500 min<sup>-1</sup>
- **Output:** 1500 W
- **Voltage:** 230 V, 16A
- **IP protection class:** 54
- **Weight with battery:** 69 kg

## Note for Germany:

According to DGUV 203-004 / 203-006, when working in conditions with increased electrical hazards – such as in wet conditions or at sockets with unknown protective measures – the use of a PRCD-S (portable residual current device with protective conductor detection) is recommended as an additional protective measure. A PRCD-S adapter is not included in the scope of delivery and can be ordered as an option if required.

## Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	P3551031220	Super Midi Miller - 230 V	<b>work range:</b> 70 - 150 mm <b>shaft typ:</b> 12 mm <b>length:</b> 20 m + 10 m <b>Power:</b> 230 volts <b>brands:</b> Picote	1122 x 712 x 466 mm 6g
	14200144	PRCD-S adaptor		1000 x 80 x 80 mm 0.30