

Pointed flexible packer 150-250

<https://ehle-hd.com/en/product/pointed-flexible-packer-150-250/>










The **Flex-Packers DN 150 - 250 mm with pointed coupling** are used in the induction process and enable easy setting of the packer. The pointed coupling overcomes even larger steps. This considerably simplifies the setting of short or long liners on long distances.

Available up to 10 m in length - special sizes on request.

Features

- the pointed and lightweight aluminum couplings ensure an easy and trouble free installation; equipped with drawbar eye and air coupling
- raw dimension \varnothing 100 mm
- red, highly extensible hose (extension max. threefold outer diameter) with friction-resistant external sheet (smooth wrap, chequered fabric)
- Temperature range between -25°C and $+60^{\circ}\text{C}$
- **max. 1.5 bar (36.2 psi) operation pressure**

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2002180	Flexible Packer pointed 150-250 / 0.8 m	length: 800 mm contact length: approx 650 - 550 mm operating pressure: 1.5 bar (21.8 psi)	800 × 100 × 100 mm 3.00
	2002181	Flexible Packer pointed 150-250 / 1.0 m	length: 1,000 mm contact length: approx 850 - 750 mm operating pressure: 1.5 bar (21.8 psi)	1000 × 100 × 100 mm 3.30
	2002182	Flexible Packer pointed 150-250 / 1.2 m	length: 1,200 mm contact length: approx 1,050 - 900 mm operating pressure: 1.5 bar (21.8 psi)	1200 × 100 × 100 mm 3.70
	2002183	Flexible Packer pointed 150-250 / 1.5 m	length: 1,500 mm contact length: approx 1,350 - 1,200 mm operating pressure: 1.5 bar (21.8 psi)	1500 × 100 × 100 mm 4.20
	2002185	Flexible Packer pointed 150-250 / 2.0 m	length: 2,000 mm contact length: approx 1,850 - 1,700 mm operating pressure: 1.5 bar (21.8 psi)	2000 × 100 × 100 mm 5.00
	2002188	Flexible Packer pointed 150-250 / 2.5 m	length: 2,500 mm contact length: approx 2,350 - 2,250 mm operating pressure: 1.5 bar (21.8 psi)	2500 × 100 × 100 mm 6.00
	2002189	Flexible Packer pointed 150-250 / 3.0 m	length: 3,000 mm contact length: approx 2,850 - 2,700 mm operating pressure: 1.5 bar (21.8 psi)	3000 × 100 × 100 mm 6.70



2002190

Flexible Packer pointed 150-250 /
4.0 m

length: 4,000 mm

contact length: approx 3,850 -
3,750 mm

operating pressure: 1.5 bar (21.8
psi)

4000 × 100 × 100
mm
8,50