

push-camera nozzle

<https://ehle-hd.com/en/product/push-camera-nozzle/>



Our **push camera nozzle** for push cables make it possible to check and simultaneously clean the basic and connection pipes in just one work step. They offer the possibility of achieving the maximum propulsion force and reach on push camera systems, even with many successive bends.

The continuous groove with clamping device is used to fasten sliding rods from various manufacturers. The camera nozzles are perfect in combination with our mobile Rohrboy high-pressure device and the mobile hose reel.

Features

- 3/8" version from 25 litres per minute (max. 40 litres per minute)
- 1/2" version from 60 litres per minute
- clamping range for push cables from 9 - 11 mm

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	19916030	3/8" push-camera nozzle	connection: 3/8" female thread application from: 80 - 200 mm water supply: from 25 lpm thrust nozzles: 4x M6 thrust jet angle: 25°	55 × 40 × 40 mm 0.37
	80-7200-C000	1/2" push-camera nozzle	connection: 1/2" female thread application from: from 100 mm water supply: from 60 lpm thrust nozzles: 6x M6 thrust jet angle: 20° front nozzles: 1x M6 front jet angle: 0°	68 × 50 × 50 mm 0.80