

## replacement cables

<https://ehle-hd.com/en/product/replacement-cables/>



The **replacement cables** are made of special steel and are particularly suitable for use in narrow pipe bends and for light work.

The replacement cables are available with and without reinforced inner core and can be used in the models drain cleaner hand machine and RAK / RIS machines with adapter pot.

## Features

- with and without inner core

## Attributes

| Image                                                                              | SKU      | Productname                                              | Attributes                                                                          | LxWxH & Weight            |
|------------------------------------------------------------------------------------|----------|----------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------|
|    | 14200110 | Replacement Cable Ø 6 / 5 m                              | <b>cable typ:</b> 6 mm<br><b>length:</b> 5 m<br><b>material strength:</b> 2.0 mm    | 200 × 200 × 30 mm<br>0.60 |
|    | 14200111 | Replacement Cable Ø 6 / 7.5 m                            | <b>cable typ:</b> 6 mm<br><b>length:</b> 7.5 m<br><b>material strength:</b> 2.0 mm  | 200 × 200 × 30 mm<br>0.90 |
|    | 14200112 | Replacement Cable Ø 8 / 7.5 m                            | <b>cable typ:</b> 8 mm<br><b>length:</b> 7.5 m<br><b>material strength:</b> 2.0 mm  | 200 × 200 × 40 mm<br>2.20 |
|  | 14200115 | Replacement Cable Ø 8 / 10 m                             | <b>cable typ:</b> 8 mm<br><b>length:</b> 10 m<br><b>material strength:</b> 2.0 mm   | 200 × 200 × 40 mm<br>2.30 |
|  | 14200114 | Replacement Cable with inner core<br>Ø 8 / 7.5 m (Kopie) | <b>cable typ:</b> 8 mm<br><b>length:</b> 7.5 m<br><b>material strength:</b> 2.0 mm  | 200 × 200 × 40 mm<br>2.30 |
|  | 14200116 | Replacement Cable with inner core<br>Ø 8 / 10 m          | <b>cable typ:</b> 8 mm<br><b>length:</b> 10 m<br><b>material strength:</b> 2.0 mm   | 200 × 200 × 40 mm<br>2.40 |
|  | 14200117 | Replacement Cable Ø 10 / 7.5 m                           | <b>cable typ:</b> 10 mm<br><b>length:</b> 7.5 m<br><b>material strength:</b> 2.5 mm | 200 × 200 × 40 mm<br>2.20 |

|                                                                                    |          |                                                           |                                                                                     |                           |
|------------------------------------------------------------------------------------|----------|-----------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------|
|    | 14200120 | Replacement Cable Ø 10 / 10 m                             | <b>cable typ:</b> 10 mm<br><b>length:</b> 10 m<br><b>material strength:</b> 2,5 mm  | 200 × 200 × 40 mm<br>3,70 |
|    | 14200118 | Replacement Cable with core Ø 10 / 7,5 m                  | <b>cable typ:</b> 10 mm<br><b>length:</b> 7,5 m<br><b>material strength:</b> 2,5 mm | 200 × 200 × 40 mm<br>2,80 |
|    | 14200121 | Replacement Cable with core Ø 10 / 10 m                   | <b>cable typ:</b> 10 mm<br><b>length:</b> 10 m<br><b>material strength:</b> 2,5 mm  | 200 × 200 × 40 mm<br>3,50 |
|    | 14200119 | Replacement Cable with 16 T-coupling Ø 10 / 7,5 m         | <b>cable typ:</b> 10 mm<br><b>length:</b> 7,5 m<br><b>material strength:</b> 2,5 mm | 200 × 200 × 40 mm<br>2,80 |
|  | 14200122 | Replacement Cable with 16 T-coupling Ø 10 / 10 m          | <b>cable typ:</b> 10 mm<br><b>length:</b> 10 m<br><b>material strength:</b> 2,5 mm  | 200 × 200 × 40 mm<br>4,00 |
|  | 14200123 | Replacement Cable with 16 T-coupling and core Ø 10 / 10 m | <b>cable typ:</b> 10 mm<br><b>length:</b> 7,5 m<br><b>material strength:</b> 2,5 mm | 200 × 200 × 40 mm<br>4,50 |