

SeeSnake Compact2 Camera System

<https://ehle-hd.com/en/product/seesnake-compact2-camera-system/>



The **SeeSnake compact2** is the next generation of the proven compact system. It offers high performance in a lightweight, compact, and rugged design. The new docking system of the CS6x VERSAMonitor allows a rotation into the position required.

- **The self-adjusting camera head** delivers sharp, clear, and, most of all, upright images.
- **Integrated distance counter and 512 Hz Flexmitter tracking transmitter** allows a precise camera head tracking.
- **Improved push cable design** - for excellent manoeuvrability

Features

performance data

- Line Capacity 1.5" to 6" (40 mm to 150 mm)
- Push Cable Length 100' (30 m)
- Push Cable Diameter 0.27" (6,7 mm)
- Push Cable Core 0.14" (3,5 mm) Fiberglass
- Push Cable Bend Minimum Radius 2.5" (63,5 mm)
- Camera Type 1" (25 mm) Self-Leveling
- Resolution 656 x 492 (NTSC), 768 X 576 (PAL)
- Light Source 6 LEDs
- Sonde 512 Hz
- Ingress Protection without Monitor IPx5



Scope of delivery

- Complete set with CS6x VERSA
- SeeSnake Compact2 reel
- CS6xPak monitor with recording function
- 4.0 Battery
- charger

page 1



Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	R48118	Compact2 with CS6x VERSA monitor	type: complete set work range: 40 - 150 mm length: 30 m locating: 512 Hz	625 × 360 × 432 mm 11.5
	R48098	Compact2 only reel	work range: 40 - 150 mm length: 30 m locating: 512 Hz	625 × 360 × 432 mm 7.5