

Small lateral packers

<https://ehle-hd.com/en/product/small-lateral-packers/>



Small lateral packers are used for repairing of the smallest diameter of house pipeline.

For easy manipulation in pipe bends the rigid ends of packer are made as short as possible. The effective surface ranges from 300 mm to 1300 mm.

Features

- For use in smallest pipe diameters Kitchen and bathroom pipes
- ISO 9001 TÜV certified

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2005130	Small lateral packer 30-40 / 0.4	work range: 30 - 40 mm length: 400 mm operating pressure: 2.5 bar (36.2 psi)	450 × 25 × 25 mm 0.30
	2005131	Small lateral packer 30-40 / 0.6	work range: 30 - 40 mm length: 600 mm operating pressure: 2.5 bar (36.2 psi)	650 × 25 × 25 mm 0.40
	2005132	Small lateral packer 30-40 / 1.0	work range: 30 - 40 mm length: 1.000 mm operating pressure: 2.5 bar (36.2 psi)	1050 × 25 × 25 mm 0.60
	2005133	Small lateral packer 30-40 / 1.5	work range: 30 - 40 mm length: 1.500 mm operating pressure: 2.5 bar (36.2 psi)	1550 × 25 × 25 mm 0.90
	2005140	Small lateral packer 35-50 / 0.4	work range: 35 - 50 mm length: 400 mm operating pressure: 2.5 bar (36.2 psi)	450 × 30 × 30 mm 0.35
	2005141	Small lateral packer 35-50 / 0.6	work range: 35 - 50 mm length: 600 mm operating pressure: 2.5 bar (36.2 psi)	650 × 30 × 30 mm 0.45
	2005142	Small lateral packer 35-50 / 1.0	work range: 35 - 50 mm length: 1.000 mm operating pressure: 2.5 bar (36.2 psi)	1050 × 30 × 30 mm 0.65



2005143

Small lateral packer 35-50 / 1.5

work range: 35 - 50 mm

length: 1.500 mm

operating pressure: 2.5 bar (36.2 psi)

1550 x 30 x 30 mm
0.95