

stainless steel test pipe plugs

<https://ehle-hd.com/en/product/stainless-steel-test-pipe-plugs/>



The **V2A test pipe plugs** with silicone rubber seal are characterized by their longevity. The closures have a passage, which makes bypassing possible. They are used for testing small pipe diameters - ideal for heating and sanitary applications.

With the silicone seal, the pipe plugs are also suitable for special applications in the food industry and the like.

Features

- with bypass for leak tests in the low-pressure range
- robust, long-life V2A design for shutting off pipelines from DN 12 to DN 100 mm for the heating and sanitary sector as well as for plant construction
- Silicone gasket also suitable for special applications in the food industry
- flame retardant and particularly temperature resistant from -70°C - 250°C
- **max. 8.0 bar (116 psi) back pressure**

Attention: from 1 bar back pressure the plugs must be secured against being pushed out.

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	2000110	stainless steel test pipe plug - Ø 16	use: 16 mm clamping range: 15.6-16.4 mm bypass: 3 mm	60 × 16 × 16 mm 0.05
	2000111	stainless steel test pipe plug - Ø 20	use: 20 mm (3/4") clamping range: 18.5-25 mm bypass: 3 mm	60 × 20 × 20 mm 0.06
	2000112	stainless steel test pipe plug - Ø 25	use: 25 mm (1") clamping range: 23.5-29 mm bypass: 4.5 mm	70 × 25 × 25 mm 0.07
	2000113	stainless steel test pipe plug - Ø 30	use: 30 mm clamping range: 28.5-35 mm bypass: 4.5 mm	70 × 30 × 30 mm 0.08
	2000114	stainless steel test pipe plug - Ø 35	use: 35 mm (1 1/4") clamping range: 33.5-40 mm bypass: 4.5 mm	70 × 35 × 35 mm 0.09
	2000115	stainless steel test pipe plug - Ø 40	use: 40 mm (1 1/2") clamping range: 38.5-45 mm bypass: 4.5 mm	80 × 39 × 39 mm 0.12
	2000116	stainless steel test pipe plug - Ø 45	use: 45 mm (1 3/4") clamping range: 43-50 mm bypass: 5.5 mm	80 × 43 × 43 mm 0.13

	2000117	stainless steel test pipe plug - Ø 50	use: 50 mm (2") clamping range: 48-55 mm bypass: 5,5 mm	80 × 48 × 48 mm 0.16
	2000132	stainless steel test pipe plug - Ø 55	use: 55 mm (2 1/4") clamping range: 53-60 mm bypass: 5,5 mm	80 × 53 × 53 mm 0.18
	2000134	stainless steel test pipe plug - Ø 60	use: 60 mm (2 1/4") clamping range: 58-66 mm bypass: 5,5 mm	80 × 58 × 58 mm 0.20
	2000136	stainless steel test pipe plug - Ø 65	use: 65 mm (2 1/2") clamping range: 63-71 mm bypass: 5,5 mm	80 × 53 × 53 mm 0.22
	2000138	stainless steel test pipe plug - Ø 70	use: 75 mm (3") clamping range: 68-76 mm bypass: 5,5 mm	80 × 68 × 68 mm 0.26
	2000140	stainless steel test pipe plug - Ø 80	use: 80 mm clamping range: 77-88 mm bypass: 5,5 mm	100 × 77 × 77 mm 0.35
	2000142	stainless steel test pipe plug - Ø 90	use: 90 mm (3 1/2") clamping range: 88-99 mm bypass: 5,5 mm	100 × 88 × 88 mm 0.45