

Trio Bomb nozzles

<https://ehle-hd.com/en/product/trio-bomb-nozzles/>



Heavy contamination is no problem for the Trio Bomb nozzles!

The Trio bomb nozzle is a special bomb nozzle with 3 jet circuits for better cleaning performance and higher traction compared to the bomb nozzles with 2 jet circuits only.

Features

- HP cleaning of heavily contaminated sewers of DN 150 and above
- for medium and long sewer distances

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	1100260	3/4" Trio Bomb nozzle T75	connection: 3/4" female thread application from: 150 - 250 mm water supply: from 120 lpm thrust nozzles: 3x 4 M6 thrust jet angle: 21° / 14° / 7° front nozzles: (-) front jet angle: (-)	100 × 75 × 75 mm 2.00
	1100263	1" Trio Bomb nozzle T75	connection: 1" female thread application from: 150 - 300 mm water supply: from 120 lpm thrust nozzles: 3x 4 M6 thrust jet angle: 21° / 14° / 7° front nozzles: (-) front jet angle: (-)	100 × 75 × 75 mm 2.00
	1100261	1" Trio-Bomb nozzle T100	connection: 1" female thread application from: 200 - 600 mm water supply: from 240 lpm thrust nozzles: 3x 4 M10 thrust jet angle: 21° / 14° / 7° front nozzles: (-) front jet angle: (-)	190 × 100 × 100 mm 7.30
	1100262	1 1/4" Trio Bomb nozzle T125	connection: 1 1/4" female thread application from: 300 - 800 mm water supply: from 340 lpm thrust nozzles: 3x 5 M10 thrust jet angle: 21° / 14° / 7° front nozzles: (-) front jet angle: (-)	240 × 110 × 110 mm 11.30