

## vCamDrain D18-HD - Inspection camera

<https://ehle-hd.com/en/product/vcamdrain-d18-hd-inspection-camera/>



The **vCamDrain D18-HD** is an inspection camera system for narrow sanitary pipes, siphons and bends from 40 - 80 mm. It connects wirelessly via WiFi to a tablet or smartphone and is controlled via the free VMC app.

The robust 18 mm stainless steel camera head with sapphire glass lens delivers high-resolution HD videos, while the flexible 9 mm push cable (20 m or 30 m) masters several 90° bends. With an integrated meter counter, controllable probe and up to 12 hours of battery life, the vCamDrain offers maximum flexibility - ideal for pipe and drain inspection professionals.

### Features

- Use in pipes from Ø 40-80 mm
- 9 mm push rod cable with lengths of 20 m or 30 m
- 1080p Full HD resolution
- Exchangeable stainless steel camera head with sapphire glass lens
- For siphons and tight 90° bends
- Integrated meter counter
- Locating probe with 3 frequencies (512 Hz, 640 Hz and 33 kHz)
- Control via app using WiFi with tablet or smartphone
- Central control via app: recordings, illumination, meter counter and locating transmitter
- Simple sending of the recordings
- Power supply: rechargeable Li-ion battery (10 h with tracking, 12 h without tracking)
- Protection class: IP65

### Scope of delivery

- vCamDrain D18-HD inspection camera
- Accessory bag
- Power supply unit and charging cable
- Centring Skids, tool, cell phone holder
- manual

[Free VMC App - Download](#)

## Attributes

| Image                                                                            | SKU            | Productname      | Attributes                                                                                    | LxWxH & Weight             |
|----------------------------------------------------------------------------------|----------------|------------------|-----------------------------------------------------------------------------------------------|----------------------------|
|  | VCD-70A-D18HD  | vCamDrain - 20 m | <b>work range:</b> 40 - 80 mm<br><b>length:</b> 20 m<br><b>locating:</b> 33 kHz 512 Hz 640 Hz | 350 × 250 × 420 mm<br>6.80 |
|  | VCD-100A-D18HD | vCamDrain - 30 m | <b>work range:</b> 40 - 80 mm<br><b>length:</b> 30 m<br><b>locating:</b> 33 kHz 512 Hz 640 Hz | 350 × 250 × 420 mm<br>7.70 |