

WV Classic - rotary sewer nozzle

<https://ehle-hd.com/en/product/wv-classic-rotary-sewer-nozzle/>



The **Warthog WV Classic** rotary nozzle easily passes through several bends and bends in small pipes from 50 - 100 mm and is used to remove roots, ice and other blockages. The head can be replaced when worn to extend the service life.

Ideal for cleaning professionals who operate high pressure pumps with low flow rates and are looking for a compact, powerful nozzle that delivers great results in small pipes with bends.

Features

- can be used in nominal pipe sizes from DN 50 to DN 100
- from 11 - 30 liters per minute
- for removing sludge clods, light incrustations, fine roots and grease deposits
- for the preparation of rehabilitation measures
- ideal for small high-pressure pumps with low water output
- the head can be easily replaced without seals or bearings requiring maintenance
- service interval 40 - 50 hours


Nozzle inserts:

- In order to optimally match the nozzle to the jetting unit, we need the power of the pump (litres per minute), the working pressure (bar) and the length, diameter and material of the HP hose.

Scope of delivery:

- Warthog WV Classic nozzle
- incl. nozzle inserts

Attributes

Image	SKU	Productname	Attributes	LxWxH & Weight
	WV-1/4-BSP	WV Classic - 1/4"	connection: 1/4" female thread application from: 50 - 100 mm water supply: 11 - 30 lpm thrust nozzles: 2x 135° operating pressure: 85 - 350 bar	51 × 38 × 38 mm 0.20